



Overview

Presentation	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Lead time	Usually in Stock

General

Provided equipment	Basic UPS signalling RS-232 cable CD with software User manual USB cable
Max runtime	4 min
Number of tare power	41 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Cable length	1.50 m
Colour	Black
Depth	28.8 cm
Height	22.3 cm
Product weight	9.3 kg
Mounting mode	Not rack-mountable
USB compatible	Yes
Width	14.5 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V full load
Inputvolt_other	220 V

	240 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	800 W
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	3 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Efficiency	88 % (full load)
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Rated power in VA	1000 VA

Conformance

Product certifications	CE
Standards	IEC 62040-1 safety IEC 62040-2 EMC/EMI

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...15000 m
Acoustic level	50 dB
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	4 h
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery voltage	24 V
Battery curve	D
Battery charger power	38 W rated
Battery power in VAh	152 VAh runtime

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10.6 kg
Package 1 Height	33 cm
Package 1 width	23.5 cm
Package 1 Length	36.5 cm

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------
