

Yamaha DXS18 Specs

PA Speaker

Configuration	Active Subwoofer
---------------	------------------

Enclosure Type	Bandpass Subwoofer
----------------	--------------------

Constant Voltage / Transformer Taps	<i>None</i>
-------------------------------------	-------------

Amplifier Power Rating	1020 W Program
------------------------	----------------

Amplifier Class	Class-D
-----------------	---------

Drivers

LF Driver	18" / 45.72 cm
-----------	----------------

LF Voice Coil	4" / 10.16 cm
---------------	---------------

Performance

Frequency Range 32 Hz to 120 Hz -10 dB

Maximum SPL 136 dB

Gain Range -20 dB to +10 dB

Protections Overcurrent, Thermal

Connectivity

Audio I/O **2 x** XLR 3-Pin Balanced Line Input
2 x XLR 3-Pin Balanced Line/High-Pass Thru/Output

Network I/O *None*

USB *None*

Wireless Connectivity *None*

Signal Processing

Crossover

High-Pass:

120 Hz

High-Pass:

100 Hz

High-Pass:

80 Hz

EQ

None

Parametric EQ

None

Semi-Parametric EQ

None

Filters

None

Alignment Delay

None

Phase Adjustment

0 / 180°

Power

AC Input Power

Universal:

100 to 240 VAC, 50 / 60 Hz

AC Power Connector

IEC

Power Consumption

100 W

Physical

Mounting

1 x M20 Pole Socket (Top)
1 x 1.38" / 35 mm Pole Socket (Top)

Handles

1 x Each Side

Cooling

Convection

Construction Material

Plywood

Dimensions

18.9 x 24.1 x 24.2" / 480 x 611 x 614 mm

Weight

79.4 lb / 36 kg

Packaging Info

Package Weight

129.6 lb

Box Dimensions (LxWxH)

33 x 32 x 27"
