

SKU: V11H988040

CLOSE ALL

## Technology

**Projection System** 3LCD Technology, RGB liquid crystal shutter

**LCD Panel** 0.61 inch with C2 Fine

## Image

**Color Light Output** 4,000 Lumen- 2,400 Lumen (economy)

**White Light Output** 4,000 Lumen - 2,400 Lumen (economy) In accordance with ISO 21118:2012

**Resolution** Full HD 1080p, 1920 x 1080, 16:9

**High Definition** Full HD

**Aspect Ratio** 16:9

**Contrast Ratio** 16,000 : 1

**Light source** Lamp

**Lamp** UHE, 230 W, 6,500 h durability, 17,000 h durability (economy mode)

**Keystone Correction** Auto vertical:  $\pm 30^\circ$ , Manual horizontal  $\pm 30^\circ$

**Colour Video Processing** 10 Bits

<b>2D Vertical Refresh Rate</b>	100 Hz - 120 Hz
<b>Colour Reproduction</b>	Upto 1.07 billion colours

---

## Optical

<b>Throw Ratio</b>	1.32 - 2.14:1
<b>Zoom</b>	Manual, Factor: 1 - 1.6
<b>Lens</b>	Optical
<b>Screen Size</b>	30 inches - 300 inches
<b>Projection Distance Wide/Tele</b>	1.76 m - 2.86 m ( 60 inch screen)
<b>Projection Lens F Number</b>	1.51 - 1.99
<b>Projection Lens Focal Length</b>	18.2 mm - 29.2 mm
<b>Projection Lens Focus</b>	Manual
<b>Offset</b>	10 : 1

---

## Connectivity

<b>USB Display Function</b>	3 in 1: Image / Mouse / Sound
-----------------------------	-------------------------------

<b>Interfaces</b>	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Wired Network, VGA in (2x), VGA out, HDMI in (2x), Composite in, Stereo mini jack audio out, Stereo mini jack audio in (2x), Cinch audio out, Microphone input, Wireless LAN IEEE 802.11b/g/n, Miracast
<b>Epson iProjection App</b>	Ad-Hoc / Infrastructure
<b>Network Protocol</b>	PJLink

---

## Advanced Features

<b>Security</b>	Kensington lock, Control panel lock, Security cable hole, Wireless LAN security, Password protection
<b>2D Colour Modes</b>	Dynamic, Cinema, Presentation, sRGB, Blackboard
<b>Other features</b>	AV Mute Slide, Automatic keystone correction, Built-in speaker, Direct Power on/off, Document Camera Compatible, Easy OSD pre-setting, Horizontal and vertical keystone correction, Network projection, OSD copy function, PC Free, Quick Corner, Split-Screen-Function, Wireless LAN capable, iProjecton set-up by QR code
<b>Video Color Modes</b>	Blackboard, Cinema, Dynamic, Presentation, sRGB
<b>Projector control</b>	via: AMX, Crestron, Control4, Extron

---

## General

<b>Power consumption</b>	327 Watt, 225 Watt (economy)
<b>Supply Voltage</b>	AC 100 V - 240 V, 50 Hz - 60 Hz

<b>Product dimensions</b>	309 x 282 x 90 mm (Width x Depth x Height)
<b>Product weight</b>	3.1 kg
<b>Noise Level</b>	Normal: 37 dB (A) - Economy: 28 dB (A)
<b>Supported Temperature</b>	Operation 5° C - 40° C, Storage -10° C - 60° C
<b>Supported Humidity</b>	<p>Operation 20% - 80%, Storage 10% - 90%</p> <p>If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.</p> <p>If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.</p>
<b>Included Software</b>	iProjection
<b>Options</b>	Document camera, External Speaker, Soft carry case, Wireless LAN unit
<b>Loudspeaker</b>	16 Watt
<b>What's in the box</b>	Main unit, Power cable, Quick Setup Guide, Remote control incl. batteries, User manual, Warranty document
<b>Room Type / Application</b>	Huddle space / Portable, Meeting room / Classroom
<b>Positioning</b>	Ceiling Mounted, Desktop
<b>Colour</b>	White

---