



### Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

### General

Provided equipment	CD with software User manual USB cable
Number of tare power	28 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Number of rack unit	4U
Depth	31.2 cm
Height	8.6 cm
Product weight	11 kg
Mounting mode	Rack-mounted
USB compatible	No
Width	43.7 cm

### Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V full load
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

## Output

Rated power in W	800 W
Maximum configurable power in W	800 W
Harmonic distortion	3 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	3 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Rated power in VA	1000 VA
Runtime at 200W	00:24:00
Runtime at 400W	00:11:00

## Conformance

Product certifications	CE
Standards	IEC 62040-1-1 IEC 62040-1-2

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...15000 m

## Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Liquid value	0
Battery curve	D
Battery charger power	129 W rated
Battery option	SRVS36RLBP-9A 1 1032 VAh SRVS36RLBP-9A 2 1548 VAh SRVS36RLBP-9A 3 2064 VAh SRVS36RLBP-9A 4 2580 VAh

## Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

### Packing Units

Package 1 Weight	13.7 kg
Package 1 Height	21.8 cm
Package 1 width	45.5 cm
Package 1 Length	55.1 cm

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------