



Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

General

Provided equipment	CD with software User manual USB cable
Number of tare power	40 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	4U
Depth	46.2 cm
Height	8.6 cm
Product weight	19 kg
Mounting mode	Rack-mounted
USB compatible	No
Width	43.7 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V full load
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	1600 W
Maximum configurable power in W	1600 W
Harmonic distortion	3 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	4 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Half load runtime	00:12:00 800 W
Output voltage	230 V
Maximum configurable power in VA	2000 VA
Rated power in VA	2000 VA
Runtime at 400W	00:26:00

Conformance

Product certifications	CE
Standards	IEC 62040-1-1 IEC 62040-1-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...15000 m

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	4 h
Liquid value	0
Battery curve	D
Battery charger power	242 W rated
Battery option	SRVS72RLBP-9A 1 1944 VAh SRVS72RLBP-9A 2 2916 VAh SRVS72RLBP-9A 3 3888 VAh SRVS72RLBP-9A 4 4860 VAh

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	22.7 kg
Package 1 Height	21.8 cm
Package 1 width	55.1 cm
Package 1 Length	70 cm

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------