

Specs

Camera

- Ultra-crystal clear image support up to 4K; CMOS Sony 4K
 - Frame rate: 4K 30fps, 1080p , 720p , 640x480, 320x240 at 60, 30, 15fps
 - SmartFrame: Automatic FOV adjustment to fit all participants
 - 16X Zoom (4X optical zoom + 4X digital zoom)
 - Auto focus: minimum working distance 1 meter
 - 86° Wide field of view
 - Back light compensation and 2D noise reduction technology for optimizing light balance in different conditions
 - Standard tripod screw holes
 - Analytics API: Enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
-

Motorized Pan and Tilt Movement

- Pan: $\pm 160^\circ$
 - Tilt: $+90^\circ$ (up) -30° (down)
 - 10 camera presets (through remote control)
 - Quiet and smooth pan and Tilt movement
-

Connectivity

- 12V power adaptor
 - Mini DIN6 for RS232 connection
 - USB Type C connector
-

Video format

- YUV, MJPEG
-

USB

- 2.0, 3.1 Gen1
 - UVC (USB Video Class) 1.1
-

Control

- IR remote control
 - VISCA/pelco P/pelco D via RS232
 - UVC/ plug-and play
 - PTZapp
-

Security and mount

- Camera mount included for wall or ceiling
 - Kensington slot
-

System requirement*

- Windows 7/8/8.1/10
 - Mac OS X 10.7 or higher
 - Google Chromebook version 29.0.1547.70, Platform 4319.79.0
-

Hardware Spec*

- 2.4GHz Intel® Core 2 Duo processor
 - 2GB RAM or more
 - USB 3.1 Gen1 port
-

PTZapp applicationpp

- Compatible with Skype™ Plugin for answering and hanging up via remote control
 - Upgrade firmware automatically or manually
 - Control camera
 - Set parameters and adjust camera ima
 - Diagnose operating status
 - View live video
 - Free download on Windows® and Mac® computer
-

Power supply

- AC 100V ~240V, 50/60Hz, 3 meters
 - Consumption: 12V, 2A
-

Environmental data

- Operation temperature: 0 ~40°C
 - Operation humidity: 20% ~80%
 - Storage temperature: -20 ~60°C
 - Storage humidity: 20% ~80%
-

Dimension

- Package dimensions: 227*189*261mm
 - Package weight: 2.54 kg
 - Camera: 97.8 x 130.7 x 171.1 mm/1.5kg
 - Remote control: 200 x 50 x 21 mm/0.09kg
-

Package contents

- Camera
 - Remote control
 - Power adapter
 - USB3.1 type-C to type-A (6ft)
 - USB3.1 type-A to type-C adapter
 - Quick-start guide
 - Metal mount, tripod screw
 - Battery
-

Optional accessories

- Mini DIN6 to RS232 adapter
 - 16ft USB 2.0 cable
-

Warranty**

- Camera : 3+2 year
 - Accessories: 1 year
-

Compatible Applications

- Adobe Connect, Blue Jeans, CyberLink U Meeting®, Cisco WebEx®, Google Hangout, GoToMeeting™, Intel® Unite™, Microsoft® Lync™, Skype™, Skype for Business, V-Cube, vMix, WebRTC, Wirecast, XSplit, ZOOM
-