

Technical Specifications

Print



Download



Output

Number of Outlets

5.0

Receptacle Style

BS 1363 United Kingdom

Input

Input frequency

50 Hz +/- 5 Hz

Number of Power Cords

1

Surge Protection and Filtering

Surge energy rating

918Joules

ts_nm_surge_response

1ns

Peak Current Common Mode

24kAmps

Peak Current Normal Mode

12kAmps

Physical

Maximum Height

56MM, 5.6CM

Maximum Width

385MM, 38.5CM

Maximum Depth

73MM, 7.3CM

Net Weight

0.72KG

Shipping weight

0.83KG

Shipping Height

58MM, 5.8CM

Shipping Width

405MM, 40.5CM

Shipping Depth

130MM, 13.0CM

Color

White

Master Carton Dimensions (Length x Width x Height)

7188 x 9525 x 10871MM

Master Carton Units

12.0

Master Carton Weight

10.49

Units per Pallet

216.0

SCC Codes

10731304313851

Environmental

Operating Temperature

0 – 40 °C

Operating Relative Humidity

0 – 90 %

Operating Elevation

0 – 3048meters

Storage Temperature

-5 – 40 °C

Storage Relative Humidity

0 – 95 (Non-condensing) %

Storage Elevation

0 – 4572meters

Conformance

Approvals

CE

Equipment protection policy

Lifetime : 50000 euros

Standard warranty

Limited Lifetime (European Union countries only)