



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual
--------------------	-------------

Physical

Cable length	1.83 m
Colour	White
Depth	7.26 cm
Height	5.58 cm
Product weight	0.67 kg
Width	38.5 cm

Input

Network frequency	50 Hz +/- 5 Hz
Plug standard	BS1363A British
Maximum input current	13 A
Switching current capacity	13 A
Input voltage	230 V

Output

Number of power socket outlets	5
Outlet standard	BS 1363 United Kingdom

Conformance

Product certifications	CE
------------------------	----

Equipment protection policy	Lifetime : 50000 euros
-----------------------------	------------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-5...40 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0.00...15240.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	40 dB
Peak current	24 kA common mode 12 kA normal mode
Surge energy rate	918 J

Packing Units

Package 1 Weight	0.79 kg
Package 1 Height	5.8 cm
Package 1 width	40.5 cm
Package 1 Length	13 cm
SCC14	10731304313882
Number of Units in Package 2	12
Package 2 Weight	10.25 kg
Package 2 Height	428.50 mm
Package 2 width	374.65 mm
Package 2 Length	282.70 mm
Number of Units in Package 3	216

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	Limited Lifetime (European Union countries only)
----------	--