

Technical Specifications

[Print](#)

[Download](#)

Output

Number of Outlets

8.0

Receptacle Style

BS 1363 United Kingdom

Input

Input frequency

50 Hz +/- 5 Hz

Number of Power Cords

1

Surge Protection and Filtering

Surge energy rating

2754Joules

Peak Current Common Mode

48kAmps

Peak Current Normal Mode

60kAmps

Physical

Maximum Height

62MM, 6.17CM

Maximum Width

327MM, 32.65CM

Maximum Depth

110MM, 11.03CM

Net Weight

0.91KG

Shipping weight

1.05KG

Shipping Height

365MM, 36.5CM

Shipping Width

170MM, 17.0CM

Shipping Depth

64MM, 6.4CM

Color

White

Master Carton Dimensions (Length x Width x Height)

387 x 213 x 365MM

Master Carton Units

6.0

Master Carton Weight

6.59

Units per Pallet

156.0

SCC Codes

10731304313592

Environmental

Operating Temperature

0 - 40 °C

Operating Relative Humidity

0 - 90 %

Operating Elevation

0 - 3048meters

Storage Temperature

-5 - 40 °C

Storage Relative Humidity

0 - 95 (Non-condensing) %

Storage Elevation

0 - 4572meters

Conformance

Approvals

CE