

Technical Specifications

[Print](#)

[Download](#)

Output

Number of Outlets

8.0

Receptacle Style

BS 1363 United Kingdom

Input

Input frequency

50 Hz +/- 5 Hz

Number of Power Cords

1

Surge Protection and Filtering

Surge energy rating

2690Joules

Data Line Protection

Coaxial cable for CATV/SATV/modem/audio-video, RJ11 modem/fax protection

Peak Current Common Mode

48kAmps

Peak Current Normal Mode

60kAmps

Physical

Maximum Height

62MM, 6.17CM

Maximum Width

327MM, 32.65CM

Maximum Depth
110MM, 11.03CM

Net Weight
1.05KG

Shipping weight
1.19KG

Shipping Height
65MM, 6.5CM

Shipping Width
365MM, 36.5CM

Shipping Depth
170MM, 17.0CM

Color
White

Master Carton Units
6.0

Master Carton Weight
7.59

Units per Pallet
156.0

SCC Codes
10731304313226

Environmental

Operating Temperature
0 – 40 °C

Operating Relative Humidity
0 – 90 %

Operating Elevation
0 – 3048meters

Storage Temperature
–5 – 40 °C

Storage Relative Humidity
0 – 95 (Non-condensing) %

Storage Elevation
0 – 4572meters
