

# Technical Specifications

[Print](#)

[Download](#)

## Output

Number of Outlets

5.0

Receptacle Style

Schuko CEE 7

---

## Input

Input frequency

50 Hz

Number of Power Cords

1

Input Power

2300 Watts

---

## Surge Protection and Filtering

Surge energy rating

918Joules

ts\_nm\_surge\_response

1ns

Peak Current Common Mode

24kAmps

---

## Physical

Maximum Height

56MM, 5.58CM

Maximum Width

370MM, 37.0CM

---

Maximum Depth

73MM, 7.3CM

Net Weight

0.67KG

Shipping weight

0.79KG

Shipping Height

58MM, 5.8CM

Shipping Width

405MM, 40.5CM

Shipping Depth

130MM, 13.0CM

Color

White

Master Carton Dimensions (Length x Width x Height)

283 x 375 x 429MM

Master Carton Units

12.0

Master Carton Weight

9.48

Units per Pallet

72.0

SCC Codes

50731304313743

## Environmental

Operating Temperature

0 – 40 °C

Operating Relative Humidity

0 – 95 (Non-condensing) %

Operating Elevation

0 – 15240meters

Storage Temperature

-15 – 45 °C

Storage Relative Humidity

0 – 95 %

Storage Elevation

0 – 15240meters

## Conformance

Approvals

CE