

# Specifications

Overview

## Lead time

Usually in Stock

General

## provided equipment

User manual

Physical

## cable length

2.00 m

## colour

White

## depth

11 cm

## height

6.2 cm

## product weight

0.75 kg

## width

27.2 cm

Input

## input power

2300 W

## network frequency

50 Hz

## plug standard

Schuko CEE 7/7P

## maximum input current

10 A

## switching current capacity

10 A

## input voltage

230 V

Output

## number of power socket outlets

6

## outlet standard

Schuko CEE 7

Conformance

## product certifications

CE

## equipment protection policy

Lifetime : 50000 euros

Environmental

## ambient air temperature for operation

0...40 °C

## relative humidity

0...95 % non-condensing

## operating altitude

0...50000 ft

## ambient air temperature for storage

-15...45 °C

## storage Relative Humidity

0...95 %

## storage altitude

## 0.0015249000 Surge Protection and Filtering

### response time

1 ns common mode

### Common mode rejection

40 dB

### peak current

48 kA common mode

### Surge energy rate

1836 J

Packing Units

### Package 1 Weight

0.89 kg

### Package 1 Height

6.5 cm

### Package 1 width

31 cm

### Package 1 Length

16.5 cm

### SCC14

10731304313721

### Number of Units in Package 2

12

### Package 2 Weight

10.68 kg

### Package 2 Height

406.40 mm

### Package 2 width

330.20 mm

### Package 2 Length

355.60 mm

### Number of Units in Package 3

96

Offer Sustainability

### Sustainable offer status

Green Premium product

### REACH Regulation

[REACH Declaration](#)

### REACH free of SVHC

Yes

### EU RoHS Directive

Compliant

[EU RoHS Declaration](#)

### Mercury free

Yes

### RoHS exemption information

Yes

### Environmental Disclosure

[Product Environmental Profile](#)

### Circularity Profile

[End of Life Information](#)

### WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins