

PANEL

Screen Size	49"
Panel Technology	IPS
Aspect Ratio	16 : 9
Native Resolution	3,840 x 2,160 (UHD, RGB)
Brightness(Typ.,cd/m ²)	350
Contrast Ratio	1,100:1
Viewing Angle (H x V)	178 x 178
Response Time	8ms (G to G)
Surface Treatment (Haze)	Haze 3%
Life Time (Typ.)	50,000 Hrs
Operation Hours	18 Hrs
Orientation	Portrait & Landscape

CONNECTIVITY

Input	HDMI (3), DP, DVI-D, Audio, USB 2.0
Output	DP, Audio (Off/Fixed/Variable)
External Control	RS232C In/out, RJ45 (LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	9.9mm(T/R/L), 14.4mm(B)
Monitor Dimension (W × H × D)	1,098.6mm x 644.5mm x 39.9mm
Weight (Head)	15.4 kg
Carton Dimensions (W × H × D)	1,197mm x 775mm x 162mm
Packed Weight	18.8 kg
Handle	No
VESA™ Standard Mount Interface	300 x 300

SPECIAL FEATURE

Tilt (Facedown)	Max. 30° *In conditions within 30°C temperature, 50% humidity
-----------------	---

IP Rating	IP5x
-----------	------

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
-----------------------	-------------

Operation Humidity	10 % to 80 %
--------------------	--------------

POWER

Power Supply	100-240V~, 50/60Hz
--------------	--------------------

Power Type	Built-In Power
------------	----------------

POWER CONSUMPTION

Typ. / Max.	85W / 120W
-------------	------------

Smart Energy Saving	65W
---------------------	-----

CERTIFICATION

Safety	CB / NRTL
--------	-----------

EMC	FCC Class "A" / CE / KC
-----	-------------------------

ErP / Energy Star	Yes(EU Only) / Yes (Energy Star 8.0)
-------------------	--------------------------------------

MEDIA PLAYER COMPATIBILITY

OPS Type Compatible	Yes
---------------------	-----

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
-----------------------------	---------------

Control and Monitoring Software	SuperSign Control/Control+
---------------------------------	----------------------------

Signage365Care	Yes
----------------	-----

ACCESSORY

Basic	Remote Controller, Power Cord, QSG, Regulation Book, Phone to RS232C Gender
-------	---

Optional	Stand(ST-653T), Media Player, Wall Bracket(LSW350B), VESA Adapter(AM-B330S), OPS Kit(KT-OPSF)
----------	---