**TECHNICAL SPECIFICATIONS**

| | |
|---|---|
| **Counting speed** | 3000 coins per minute |
| **Coin size Range** | <ul><li>Diameter: 15.0 to 32.4 mm</li><li>Thickness: 1.0 to 3.0 mm</li><li>Differential: 0.5 mm minimum</li></ul> |
| **Tilting inspection pan capacity** | Up to 4500 coins |
| **Coin feed (hopper) capacity** | Up to 1500 coins |
| **Currencies** | GBP, other currencies avilable on request |
| **Sorting capability** | Up to 8 different denominations |
| **Exact bag stops** | Three selectable bag stops per denomination |
| **Display** | LCD, two line, alpha-numeric |
| **Connectivity** | <ul><li>2 RS232 ports</li><li>1 USB-B port</li><li>1 RJ11 Printer</li></ul> |
| **Power supply** | 90 – 264V AC, 50/60 Hz |
| **Power consumption** | 140W |
| **Dimensions (H × W × D)** | 288 × 425 × 552 mm |
| **Weight** | 21.4 kg |
| **Manufacturing standards & approvals** | ISO9001, CE, CUL |
| **Security features** | <ul><li>Lockout security to protect operating information</li><li>Battery back up in the event of power failure</li></ul> |