

Specifications

Hopper Capacity	600pcs
Stacker Capacity	200pcs
Currency Support	5 currencies(Standard) 40 currencies(Option)
Display	Color TFT-LCD (3.5 inch),Touch Screen
Suitable Note Size	Length: 100mm~175mm
	Width: 50mm~90mm
Suitable Note Thickness	0.05mm~0.12mm
Speed (pcs / min)	800,1000,1200 (SDC MIX mode)
	800,1000 (serial number reading mode)
RAM	1G
Batch Number	5-200pcs
Connectivity	USB for data collection and software upgrade
	RS232 for PC communication
	RJ 12 for external display
	WLAN for data collection and software upgrade in batch
	SD card for data storage
Counterfeit Detection	Ultraviolet detection(UV)
	Magnetism detection(MG)
	Metal thread detection(MT)
	Infrared image detection(IR)
	CIS image detection (double sides)
Counting modes	Piece counting (CNT)
	Value counting (SDC, MIX)
	Auto recognition
	Multi-currency mix counting
	Batch (5-200)
	Accumulation
Language Support	Different language for user's selection
Power Supply	AC 220V 50Hz \pm 10%
	AC 110V 60Hz \pm 10%

Noise level	60-75DB
Power consumption	Standby \leq 15W
	Operation \leq 50W

Working environment	Environment temperature (0~40°C)/humidity (40~90%) Air pressure (70-106kpa)
Storage environment	Environment temperature (-40~55°C)/humidity (10~95%) Air pressure (70-106kpa)

Packing Details

Machine Dimensions(WxDxH)	287(H)x240(W)x232(D)mm
Net Weight	5.9kg
Transportation Packing	2units/carton
Transport Carton Dimension	380(H)x650(W)x350(D)mm
Gross Weight/carton	16kg