

Technical Specification

Display and Sound	<ul style="list-style-type: none">• 10.1" LCD wide aspect ratio• 300 nits maximum brightness• 1280 x 800 high resolution• View angle: 170 x 170• Built-in stereo speakers 1 W x 2• HDMI output to external display
Content Management	<ul style="list-style-type: none">• SignApps Express• 3rd party solution (optional license)
Open Standards Supported	<ul style="list-style-type: none">• HTML5 Javascript and CSS• Android 7.1 API• W3C SMIL for cross-platform management• W3C widgets for HTML delivery• POPAI digital signage content standards, include:<ul style="list-style-type: none">• S1 (JPEG 480p baseline)• S2 (JPEG 720p baseline)• S4 (MPEG L2 audio)• S5 (MP3 audio, 84 Kpbs)• S6 (MPEG-1 SIF, 3 Mbps CBR)• S7 (MPEG-1 480p, 10 Mbps CBR)• S8 (MPEG-1 720p, 15 Mbps CBR)• S9 (MPEG-2 480p, 6 Mbps CBR)• S10 (MPEG-2 720p, 12 Mbps CBR)• S11 (H.294 / MPEG-4 AVC, 480p, 6 Mbps CBR)• S12 (H.264 / MPEG-4 AVC, 720p, 10 Mbps CBR)• E1 (PNG 24 bpp + alpha, 480p)• E2 (PNG 24 bpp + alpha, 720p)• E4 (VC-1 / WMV9, MP@ML, 720p)• E7 (MPEG-4 ASP, 480p, 10 Mbps CBR)• E8 (H.264 / MPEG-4 AVC, 1080p, 20 Mbps CBR)
HTML5 Support	<ul style="list-style-type: none">• Widgets for calendar, clock, news, and web page integration• HTML5 technology including CSS and Javascript• Chromium-based browser engine, same as Google Chrome™
Advanced Signage Features	<ul style="list-style-type: none">• Remote commissioning• AlwaysOn, AppLock to prevent unauthorized access• StrongCache for continuous playback even when network is not available
Connectivity	<ul style="list-style-type: none">• Wi-Fi: 802.11 b/g/n• Ethernet 10/100 BASE-T• 3.5 mm analog stereo audio out• USB 2.0 x 2• Micro USB for ADB• Optional 3G / 4G mobile module via USB
Mounting Options	<ul style="list-style-type: none">• Built-in VESA compatible 100 mm x 100 mm posts• Built-in VESA and flush mount• PGM-001 glass mount• PTM-101 VESA tilt mount• PVK-102 pivot table stand• PWM-040 window mount

Supplied Accessories	<ul style="list-style-type: none"> • Table stand • Adapter • Power plug • Vandal-proof I/O bracket • Hardware quick guide
Power Requirement	<ul style="list-style-type: none"> • Input: 100 - 240 V, 50 - 60 Hz, 0.5 A max. • Output: 12 V, 1.5 A • UL / CB certified power supplies • Interchangeable connector system includes US plugs (optional for EU, UK, and AUS plugs)
Environmental	<ul style="list-style-type: none"> • Operating temperature: 0 °C to 40 °C • Humidity: 10 % to 85 % @ 40 °C non-condensing
Dimensions for Product & Package	<ul style="list-style-type: none"> • Display size (mm): 269.88 x 170.77 x 28.5 (10.62" x 6.72" x 1.12") • Display weight (g): 692 (1.52 lbs) • Individual package size (mm): 336 x 100 x 227 (13.2" x 3.93" x 8.93") • Outer carton size (mm): 695 x 260 x 530 (27.36" x 10.23" x 20.86") • Units per outer carton: 10
Certifications	<ul style="list-style-type: none"> • CE / FCC / IC / RCM