

Mixer Specification

| | |
|-------------------------------|---|
| Model | Xone:PX5 |
| Type | Analog |
| Channels | 4 + 1 |
| EQ | 3-band / Total Kill (CH 1-4 + CH A) |
| USB Soundcard | 20 Channel (10 in / 10 out) USB2 / Class Compliant 24bit / 96kHz 1 x MIDI IN 1 x MIDI Out |
| Line Inputs | 4 x RCA (CH 1-4) 1 x 1/4" TRS (CH A) Mono/Stereo |
| Phono Inputs | 4 x RCA (CH 1-4) LN/PH Switch for DVS |
| USB Inputs | 5 x USB (CH 1-4 + CH A) |
| Mic Input | 1 x XLR |
| Master Output | 1 x XLR (Balanced) |
| Master 2 Output | 1 x RCA (Un-balanced) |
| Booth Output | 1 x 1/4" TRS |
| Record Output | 1 x RCA (Un-balanced) |
| Master Insert | 1 x 1/4" TRS |
| MIDI Sync/Out | 1 x 5-Pin DIN DIN Offset Control |
| Send/Return I/O | 1 x 1/4" TRS Send 1 x 1/4" TRS Return 1 x LN/Hi-Z Switch |
| Internal Xone:FX | Yes |
| Hybrid FX Mode | Yes (Internal < Dual > External) |
| FX Send | 1 x Pre/Post Selectable (CH 1-4 + CH A) |
| Filter | 1 x VCF Filter HPF / BPF / LPF Adjustable Frequency & Resonance Assignable CH 1-4 + CH A + External Return |
| X-Link | 1 x RJ45 |
| Headphones | 1 x 1/4" 1 x 3.5mm Split Cue Monitoring |
| Channel Faders | 60mm VCA / Replaceable |
| Chanel Meters | 12 Segment LED |
| Channel Fader Curve | 3 Types |
| X-Fader | 45mm VCA / Replaceable / Innofader Compatible |
| X-Fader Curve Settings | 3 Types |
| MIDI Clock | Send + Receive Start / Stop / Pause / Tempo Bend (-/+) |
| MIDI Assignable | Yes (MIDI CC / MIDI Notes) |
| BPM Detection | Auto / Manual / Tap Tempo |
| Earth Ground Terminals | x 2 |
| Headroom | 20dB 100 to 240V |
| AC Mains | AC 50/60Hz Consumption 35W max |
| Mains Adaptor | 3 pin IEC socket with cable clamp |
| Fuse Rating | 250V AC T1AL 20mm |
| Height | 4.3" |
| Width | 12.6" |
| Depth | 14.8" |
| Weight | 11.5 lbs. |