

Tech Specs

Digital Audio	Converters: Cirrus Logic, 24-bit PCM, 48 kHz Digital Signal Processing: 32-bit, floating point, double precision Dynamic Range (A-weighted, unity gain): <ul style="list-style-type: none">• ADC: 113 dB• DAC: 113 dB• CD Input to Analog Output: 110 dB• CD Input to USB Output: 113 dB• USB Input to Analog Output: 113 dB
Inputs	2x XLR / 1/4" (6.35 mm) TRS Combo (Mic 1–2) 1x RCA stereo pair (Aux) 2x RCA stereo pairs (CD/Phono 1-2)
Outputs	2x XLR (Main) 2x XLR (Booth) 1x RCA stereo pair (Master) 1x 1/4" (6.35 mm) TRS (Headphones) 1x 1/8" (3.5 mm) TRS (Headphones)
Pads	16x velocity-sensitive multi-color back-lit pads (8 per deck, 5 modes each)
Faders	1x MAG FOUR tension-adjustable crossfader with independent Contour and Reverse controls 2x Standard channel faders with shared Contour and Reverse controls
Connections	2x XLR outputs (Main) 2x XLR outputs (Booth) 1x RCA stereo output pair (Master) 2x XLR / 1/4" (6.35 mm) TRS inputs (Mic 1–2) 2x RCA stereo input pairs (Deck 1–2) 1x RCA stereo input pair (Aux) 1x 1/4" (6.35 mm) TRS output (Headphones) 1x 1/8" (3.5 mm) TRS output (Headphones) 2x USB Type-B ports 1x IEC power cable input

Power Connection: IEC
Voltage: 100–240V, 50/60 Hz
Consumption: 50 W

Dimensions Dimensions (wxdxh): 26.5" x 13.6" x 4.9" (674 x 345 x 124.3 mm)

Weight 23.55 lbs. (10.68 kg)