

Tech Specs

Display	Full-color display with capacitive multi-touch (2.1" x 3.7" / 54 x 95 mm (wxd)) (4.3" / 109 mm (diagonal))
Pads	16x velocity-sensitive multi-color back-lit pads (8 per deck, 10 modes each)
Faders	3x MAG FOUR tension-adjustable faders (2 channel/line faders, 1 crossfader)
Outputs	2x XLR (Main) 2x 1/4" (6.35 mm) TRS (Booth) 1x RCA stereo pair (Session) 1x 1/4" (6.35 mm) TRS (Headphones) 1x 1/8" (3.5 mm) TRS (Headphones)
Inputs	4x RCA stereo pairs (Deck 1–2) 2x XLR / 1/4" (6.35 mm) TRS (Mic 1–2) 1x RCA stereo pair (Session) 1x 1/4" (6.35 mm) TRS (Footswitch)
Connections	2x USB Type-A ports (Deck 1–2 USB Controllers) 2x USB Type-B ports 1x IEC power cable input
Digital Audio	Converters: AKM High Definition Audio; 24-bit PCM, 48 kHz Digital Signal Processing: 32-bit, floating point, double precision Dynamic Range (A-weighted, unity gain): <ul style="list-style-type: none">• ADC: 114 dB• DAC: 114 dB• CD Input to Analog Output CD: 111 dB• Input to USB Output USB: 114 dB• Input to Analog Output: 114 dB
Power	Voltage: 100–240V, 50/60 Hz Consumption: 30 W
Dimensions	Dimensions (wxdxh): 11.2" x 17.5" x 4.13" (28.5 x 44.5 x 10.5 cm)
Weight	12.3 lbs. (5.6 kg)