

# Shure MV7X Specs

## Microphone

---

Primary Applications Podcast, Audio for Video

---

Form Factor Stand/Boom Mount

---

Intended Sound Sources Vocals

---

Sound Field Mono

---

Operating Principle Pressure Gradient

---

Capsule **1 x** Dynamic

---

Polar Pattern Cardioid

---

Orientation End Address

---

Circuitry Solid-State

---

Pad *None*

---

High-Pass Filter *None*

---

Tone Adjustment *None*

---

Gain Adjustment *None*

---

Indicators *None*

---

On-Board Controls *None*

---

Windscreen Built-In

---

## Performance

---

Frequency Range 50 Hz to 16 kHz

---

Off-Axis Rejection	2 dB at 60° 12 dB at 120° >20 dB at 180°
--------------------	--

---

Impedance	252 Ohms at 1 kHz
-----------	-------------------

---

Sensitivity	-55 dBV at 1 kHz (Min Gain)
-------------	-----------------------------

---

## Connectivity

---

Output Connectors (Analog)	<b>1 x</b> XLR 3-Pin Male (on Mic)
----------------------------	------------------------------------

---

Headphone Connector	<i>None</i>
---------------------	-------------

---

## Power

---

## Physical

---

Color	Black
-------	-------

---

Mounting	5/8"-27 Female (via Integrated Hardware)
----------	--

---

Included Case	<i>None</i>
---------------	-------------

---

Included Filters	<i>None</i>
------------------	-------------

---

Construction Material	Metal
-----------------------	-------

---

Dimensions	ø: 2.62 x L: 6.05" / ø: 6.65 x L: 15.37 cm (Microphone) H: 6.46 x W: 3.55 x L: 6.05" / H: 16.41 x W: 9.02 x L: 15.37 cm (Microphone, with Mount)
------------	--

---

Weight	1.21 lb / 0.55 kg
--------	-------------------

---

## Packaging Info

---

Package Weight	1.855 lb
----------------	----------

---

Box Dimensions (LxWxH)

10.7 x 5.1 x 4.4"

---

---