

Crown Audio DCI4X600 Specs

Number of Channels 4

Power Rating

2 Ohms:
300 W per Channel

4 Ohms:
600 W per Channel
600 W Bridged

8 Ohms:
600 W per Channel
1200 W Bridged

16 Ohms:
300 W per Channel
1200 W Bridged

70 V / 100 V:
600 W per Channel

140 V / 200 V:
1200 W Bridged

Load Impedance / Voltage

Parallel/Stereo:
2 / 4 / 8 / 16 Ohms
70 / 100 V

Bridged/Mono:
4 / 8 / 16 Ohms
140 / 200 V

Performance

Damping Factor > 1000

Input Impedance 10 Kilohms (Balanced)
5 Kilohms (Unbalanced)

Max Gain 34 dB

SNR > 108 dB (at 8 Ohms)

THD	< 0.35% (Full Range, at Rated Power)
-----	--------------------------------------

Intermodulation Distortion	≤ 0.35%
----------------------------	---------

Crosstalk	> 80 dB (Below Rated Power, 1 kHz)
-----------	------------------------------------

CMRR	> 70 dB
------	---------

Connectivity

I/O	Terminal Block 3-Pin Barrier Strip Output
-----	--

Power

AC Input Power	100 to 240 VAC, 50 / 60 Hz
----------------	----------------------------

AC Power Connector	IEC 15 A
--------------------	----------

Physical

Cooling	Fan (Variable Speed)
---------	----------------------

Dimensions	19.0 x 3.5 x 14.3" / 48.3 x 8.9 x 36.2 cm
------------	---

Weight	20.1 lb / 9.1 kg
--------	------------------
