

Numark M6 Specs

Number of Channels **4 x Stereo**

EQ **4 x Channel EQ:**
Low: -32 to +12 dB at 60 Hz
Mid: -32 to +12 dB at 1.2 kHz
Hi: -28 to +10 dB at 15 kHz
Mic EQ:
Low: ±12 dB at 100 Hz
Mid: ±10 dB at 1.2 kHz
Hi: ±12 dB at 15 kHz

Performance Controls Voice Ducking

Built-In Effects *None*

Connectivity

Audio Inputs **4 x Stereo RCA Line Input**
2 x Stereo RCA Phono Input
1 x XLR 3-Pin Mic Input
1 x 1/4" Mic Input

Audio Outputs **2 x XLR 3-Pin Unbalanced Master Output**
1 x Stereo RCA Unbalanced Master Output
1 x Stereo RCA Unbalanced Booth Output
1 x Stereo RCA Unbalanced Record Output
1 x 1/4" TRS Headphone Output

USB **1 x USB Type-B**

Performance

Frequency Response

Line:
20 Hz to 20 kHz ± 0.5 dB
Mic:
20 Hz to 15 kHz ± 0.5 dB
Phono:
20 Hz to 20 kHz ± 1 dB (RIAA Curve)

Input Level

Line:
77 mVrms (for +4 dBu Output)
Mic:
1.1 mVrms (for +4 dBu Output)
60 mVrms (Max)
Phono:
1.3 mVrms (for +4 dBu Output, 1 kHz)

Output Level

6.7 Vrms (Max)

Headphone Output Power

500 mW into 47 Ohms

I/O Impedance

Line Input:
10 Kilohms
Mic Input:
600 Ohms (Unbalanced)
Phono Input:
47 Kilohms

SNR

Line:
>96 dBA (Max Output)
Mic:
>94 dBA (Max Output)
Phono:
>79 dBA (Max Output)

THD

<0.01%

Compatibility

OS Compatibility

macOS
Windows

Power

Power Consumption

9.1 W (Typical)
11.6 W (Maximum)

Physical

Dimensions (W x D x H)

12.6 x 14.2 x 4.0" / 32.1 x 36.2 x 10.2 cm

Weight

9.6 lb / 4.4 kg

Packaging Info

Package Weight

12.5 lb

Box Dimensions (LxWxH)

17 x 16.5 x 7"
