

Input Formats

480/59.94i, 576/50i, 480/59.94p, 576/50p, 720/59.94p, 720/50p, 1080/59.94i, 1080/50i, 1080/59.94p, 1080/50p, 640 x 480, 800 x 600, 1024 x 768, 1280 x 768, 1280 x 1024, 1366 x 768, 1400 x 1050, 1600 x 1200, 1920 x 1200

*RGB formats : Conforms to VESA DMT Version 1.0 Revision 11.

*The maximum refresh rates of RGB is 75 Hz. (excluding 1600 x 1200 and 1920 x 1200. The refresh rate of these 2 is 60Hz)

*1920 x 1200/60Hz : Reduced blanking

Audio Formats

The maximum is PCM 8ch, Dolby Digital, True HD DTS-HD Master Audio

Input Connectors

HT-TX01: HDMI x 1 : Type A 19 pins

HT-RX01: RJ45 x 1

Output Connectors

HT-TX01: RJ45 x 1

HT-RX01: HDMI x 1 : Type A 19 pins

Other Connectors

RS-232 x 1 : 9 pins D-sub type

*when using additional RS-232 cable

Transmission distance

The maximum is 100m (328 ft)

*To make connections, use a Cat 5e (Category 5e) or later shielded LAN cable.

*The available distance depends on the quality of the LAN cable.

Operating temperature range

0 to 40 degree C

32 to 104 degrees F

Operating temperature humidity

10 to 85 % (no condensation)

Storage temperature range

20 to 60 degree C

4 to 140 degrees F

Storage temperature humidity

10 to 85 % (no condensation)

Current Draw

2 A

Power Supply

AC Adaptor

Dimensions

81 (W) x 93 (D) x 24 (H) mm

3-3/16 (W) x 3-11/16 (D) x 1 (H) inches

Weight excl. AC adaptor

300 g

11 oz

Accessories

AC adaptor

AC plugs (3 types)

RS-232 conversion cable (2 m (6 ft 6 inches))

ferrite core x 3

Owner's Manual

Size and Weight

Width

81 mm

3-1/4 inches

Depth

93 mm
3-11/16 inches

Height

24 mm
1 inches

Weight

300 g
0 lbs. 11 oz.