

# Yamaha EMX5014C Specs

Power Rating	500W + 500W (4ohms) 370W + 370W (8ohms/ AC100V model) 350W + 350W (8ohms/ AC120V model) 320W + 320W (8ohms/ AC220-240V model)
Mic/Line Inputs	Balanced 1/4" TRS Phone Line Mono x6 Balanced XLR Microphone x8 Balanced 1/4" TRS Phone Stereo Paired x4 Unbalanced RCA Phono Stereo Paired x2
Mains Inputs	No
In-Line Inputs>Returns	No
Aux Sends	1/4" TRS Stereo Phone x3
Aux Returns	No
Inserts	1/4" TRS Phone <i>all mono input channels</i>
BUS (Group) Outputs	Stereo
Main Output	Locking 1/4" & XLR Combo-Connectors x2 1/4" Phone Connectors x2
Tape I/O	RCA Phono
Monitor Outputs	1/4" TRS Phone Output x2

EQ Section	HIGH: 10kHz (Shelving) MID(MONO): 250Hz-5kHz (Peaking) MID(ST) 2.5kHz (Peaking) LOW: 100Hz (Shelving)
Solo/Mute	Mute and PFL on all input channels
Channel Level Control	Fader
Trim/Gain Control	Rotary Controls
Phantom Power	+48V group switched on CH1-6,7 / 8,9 / 10
Metering	12-segment peak led
Frequency Response	0, +0, -3dB, 20Hz-20kHz, 0dB @1kHz
Signal-to-Noise Ratio	-128dBu
Total Harmonic Distortion (THD)	Less than 0.3%, +14dBu output into 600ohms
Power Supply	Japan: AC100V 50/60Hz, 500W North America: AC120V, 60Hz, 500W Other Areas: AC220-240V, 50/60Hz, 500W
Dimensions	17.48 x 6.10 x 19.40" (444 x 155 x 493mm)
Weight	23.14 lbs (10.5kg)

## Packaging Info

Package Weight	28.3 lb
----------------	---------

---

Box Dimensions (LxWxH)

24 x 21 x 11"

---