

SPECIFICATIONS

Model:	XE-A137 XE-A147	
Dimensions:	335 (W) x 360 (D) x 190 (H) mm	
Weight:	Approx. 5 kg	
Power Source:	Official (nominal) voltage and frequency	
Power Consumption:	Stand-by: 1.9 W (The official voltage: 220 to 230V [50Hz/60Hz] and 230 to 240 V [50 Hz]) Operating: 8.1 W (The official voltage: 220 to 230 V [50Hz/60Hz] and 230 to 240 V [50 Hz])	
Working Temperature:	0 to 40 °C (32 to 104 °F)	
Humidity:	20 % to 90 %	
Electronics:	LSI (CPU) etc.	
Display:	7-segment display (9 positions)	
Printer:	Type:	One-station thermal printer
	Printing speed:	Approx. 7 lines/second
	Printing capacity:	30 digits
	Other functions:	- Logo message function - Receipt (ON-OFF) function
Logo:	Graphic logo printing:	
	Size:	130 (H) x 360 (W) pixel Area of black must be less than 35% of all area.
	Logo message printing:	
	Logo message for the receipt (max. 30 characters x 6 lines)	
Paper Roll:	Width: 57.5 ± 0.5 mm Max. diameter: 80 mm Quality: High quality (0.06 to 0.08 mm thickness)	
Cash Drawer:	3 slots for bills and 6 for coin denominations	
Accessories:	Basic user manual:	1 copy
	Paper roll:	1
	Mode key (same as drawer lock key):	2
	AC adapter:	1
	Fiscal caution sheet:	1 (for Germany and Norway)

*Specifications and appearance are subject to change without notice for improvement.

■ Option

The following sharp option is available only for your XE-A147 register.

- Option battery model XE-A1BT