

Mackie MP-460 Specs

Headphone

Earpiece Design	In-Ear (Intra-Aural), Closed-Back
-----------------	-----------------------------------

Earpiece Connection / Wearing Style	Ear Clip, Wired
-------------------------------------	-----------------

Driver Type	Balanced Armature
-------------	-------------------

Number of Drivers	4, per Earpiece
-------------------	-----------------

Impedance	32 Ohms
-----------	---------

Active Noise Cancellation	No
---------------------------	----

Controls/Microphone Location	Controls: Cable
------------------------------	-----------------

Performance

Frequency Response	20 Hz to 20 kHz
--------------------	-----------------

Sensitivity	94 dB at 1 kHz
-------------	----------------

Volume Limiting	<i>None</i>
-----------------	-------------

Noise Attenuation	Up to 40 dB (Passive)
-------------------	-----------------------

Wired Connectivity

Audio Connector to Source	1 x 1/8" / 3.5 mm TRRS Male Right-Angled
---------------------------	---

Connector Plating	Gold
-------------------	------

Adapter (Included)	1/4" TRS
--------------------	----------

Cable Design	Y-Type, Braided, Detachable
--------------	-----------------------------

Audio Connector to Earpiece	2 x MMCX Male
-----------------------------	----------------------

Cable Color	Black, Silver
-------------	---------------

Physical

Water Resistance	<i>None</i>
------------------	-------------

IP Rating	<i>None</i>
-----------	-------------

LED Indicator	<i>None</i>
---------------	-------------
