

# Mackie CR8S-XBT Specs

## Studio Monitor

---

Monitor Type	Active Subwoofer
--------------	------------------

---

Enclosure	Bass-Reflex
-----------	-------------

---

Power Rating	200 W
--------------	-------

---

Drivers	<b>1 x</b> 8" / 20.32 cm Polypropylene Woofer
---------	---

---

Amplification	<b>1 x</b> Subwoofer: 200 W Peak
---------------	----------------------------------

---

## Performance

---

Phase Adjustment	Phase Inversion 0 / 180°
------------------	--------------------------

---

## Signal Processing

---

EQ	<i>None</i>
----	-------------

---

Filters	<i>None</i>
---------	-------------

---

Parametric EQ	<i>None</i>
---------------	-------------

---

## Crossover

---

Crossover Frequency	Low-Pass: 40 Hz Low-Pass: 80 Hz Low-Pass: 120 Hz Low-Pass: 180 Hz
---------------------	--

---

## Connectivity

---

Audio I/O	<b>2 x</b> 1/4" TRS Balanced/Unbalanced Female Analog Input <b>1 x</b> 2RCA Unbalanced Female Analog Input <b>2 x</b> 1/4" TRS Balanced/Unbalanced Female Analog Output <b>1 x</b> 2RCA Unbalanced Female Analog Output <b>1 x</b> 1/4" TRS Unbalanced Female Analog Input
-----------	--

---

## Power

---

AC Input Power	100 to 240 VAC, 50/60 Hz
Power Consumption	150 W

---

## General

---

Enclosure Material	Wood
Mounting Points	<i>None</i>

---