

- **Display**
 - **Screen Size**49 inch
 - **Backlight** Direct-lit LED backlight
 - **Pixel Pitch**0.56 mm
 - **Physical Seam**3.5 mm
 - **Bezel Width**2.3 mm (top/left), 1.2 mm (bottom/right)
 - **Resolution**1920 × 1080@60 Hz (downward compatible)
 - **Brightness**500 cd/m²
 - **Active Display Area**1074.24 (H) mm x 604.26 (V) mm
 - **Viewing Angle**Horizontal 178°, vertical 178°
 - **Color Depth**8 bit, 16.7 M
 - **Contrast Ratio**1200:1
 - **Response Time**8 ms (G to G)
 - **Color Gamut**72% NTSC
 - **Surface Treatment**Haze 25%, 3H
-

- **Interface**

- **Video & Audio Input**HDMI × 1, DVI × 1, VGA × 1, DP× 1, USB × 1

- **Video & Audio Output**HDMI × 1

- **Control Interface**RS232 IN × 1, RS232 OUT × 1

- **Power**

- **Power Supply**100-240 VAC, 50/60 Hz

- **Power Consumption**≤ 134 W

- **Standby Consumption**≤ 0.5 W

- **Working Environment**

- **Working Temperature**0°C to 40°C (32°F to 104°F)

- **Working Humidity**10% to 80% RH (non-condensing)

- **Storage Temperature**-20°C to 60°C (-4°F to 140°F)

- **Storage Humidity**10% to 90% RH (non-condensing)

- **General**

- **Casing Material**SECC

- **VESA**600 (H) mm × 400 (V) mm
- **Product Dimension (W × H × D)**1078.34 mm × 608.36 mm × 72.8 mm
(42.45" × 23.95" × 2.87")
- **Package Dimension (W × H × D)**

Carton with two displays: 1289 mm × 813 mm × 424 mm (50.75" × 32.01" × 16.69")

Carton with a single display: 1289 mm × 813 mm × 424 mm (50.75" × 32.01" × 16.69")

-
- **Net Weight**21.89 ± 0.5 kg (48.26 ± 1.1 lb) for single display
 - **Gross Weight**

Carton with two displays: 54.1 ± 0.5 kg (119.23 ± 1.1 lb)

Carton with a single display: 26.86 ± 0.5 kg (59.22 ± 1.1 lb)

-
- **Packing List**LCD display × 1, power cable × 1, network cable × 1, 2-meter HDMI cable × 1, screw × 4, remote control × 1, IR receiver × 1, RS-232

converter × 1, quick start guide (multilingual) × 1, quick start guide

(English) × 1
