

Projector type	1-Chip DLP Laser	
Power	AC 100–240 V, 50/60 Hz	
Power consumption^{*1}	880 W	
Lens	Powered zoom (throw ratio 1.7–2.4:1), powered focus F 1.7–1.9, f 25.6–35.7 mm	
Resolution	4,608,000 pixels / 2715 x 1697 dots * With Smooth Pixel Drive: ON.	
Center-to-Corner Uniformity^{*3}	90%	
DLP™ Chip		
Panel Size	17.0 mm (0.67 in) diagonal, 16:10 aspect ratio	
Display Method	DLP™ chip x 1, DLP™ system	
Pixels	2,304,000 (1920 x 1200) pixels	
CONTRAST	10,000:1 (Full On/Full Off) * With [Dynamic Contrast] set to [3].	
Screen size (diagonal)	1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 16:10 aspect ratio	
Lens Shift		
Vertical	+50 %, -16 % (+40%, -16% with ET-DLE060) (powered)	
Horizontal	+30 %, -10 % (+19%, -10% with ET-DLE060 / +28 %, -10 % with ET-DLE085/ET-DLE105)	

	(powered)
Keystone correction range	Vertical: $\pm 40^\circ$ ($\pm 5^\circ$ with ET-DLE020, $\pm 16^\circ$ with ET-DLE060, $\pm 22^\circ$ with ET-DLE105/ET-DLE085/ET-DLE055, $+5^\circ$ with ET-DLE035), Horizontal: $\pm 15^\circ$ ($\pm 10^\circ$ with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)
Installation	Ceiling/floor, front/rear, free 360-degree installation
Operating noise*1	40 dB (Normal)/38 dB (Quiet)
Light source	Laser diode
Light Output	8,000 lm ^{*1} / 8,400 lm (Center) ^{*2}
Time until light output declines to 50 %*3	20,000 hours (NORMAL)/24,000 hours (ECO)
Cabinet Materials	Molded plastic
Dimensions (WxHxD)	498 x 200 ^{*6} x 581 mm (19 19/32" x 7 7/8" ^{*6} x 22 7/8") (with supplied lens)
Operating Environment	Operating temperature: 0 °C- 45 °C (32 °F -113 °F)*7, operating humidity: 20 %-80 % (no condensation)
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit, ET-CUK10 Auto Screen Adjustment Kit), Smart Projector Control for iOS/Android™
Terminal	
SDI IN	BNC x 1: 3G/HD-SDI input
HDMI In	HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K signal input)
DVI-D In	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
MULTI PROJECTOR SYNC IN	BNC x 1
MULTI PROJECTOR SYNC OUT	BNC x 1

Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Serial Out	D-sub 9-pin (male) x 1 for link control
Remoter 1 In	M3 jack x 1 for wired remote control
Remoter 1 Out	M3 jack x 1 for link control (for wired remote control)
Remoter 2 In	D-sub 9-pin (female) x1 for external control (parallel)
LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PJLink™ [Class 2], Art-Net)
DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX (Compatible with PJLink™ [Class 2], Art-Net, HDCP 2.2, Deep Color, 4K signal input)
USB	USB Connector (Type A) x 1 for Cloning/Wireless Module (output 5 V/500 mA)
Expansion Slot	Open slot for SLOT NX compatible interface board