

DISPLAY SIZE (DIAGONAL)	21.5"
ASPECT RATIO	16:9
NATIVE RESOLUTION	FHD (1920 x 1080)
PIXEL PITCH	0.247 mm
PIXELS PER INCH (PPI)	102 ppi
SCREEN TREATMENT	Anti-glare
BRIGHTNESS	250 nits
CONTRAST RATIO	1000:1
DISPLAY CONTRAST RATIO (DYNAMIC)	8000000:1
CURVATURE	Flat
BACKLIGHT TYPE	Edge-lit
DETACHABLE STAND	Yes
HEIGHT ADJUSTMENT RANGE	No height adjust
BEZEL	3-sided micro-edge
HORIZONTAL VIEWING ANGLE	178°
VERTICAL VIEWING ANGLE	178°
TOUCH-ENABLED	Not touch-enabled
RESPONSE TIME (TYPICAL)	5ms GtG (with overdrive)
TILT	-5 to +23°
SWIVEL	No swivel
DISPLAY FEATURES	Asset control On-screen controls Plug and Play User controls

	Low blue light mode Anti-glare
HARDNESS	3H
FLICKER-FREE	Yes
PANEL BIT DEPTH	8 bit (6 bit + 2 FRC)
PIVOT	No pivot
LOW BLUE LIGHT	Yes (TÜV certified)
VESA MOUNTING	100 mm x 100 mm
INTEGRATED PRIVACY FILTER	No
PHYSICAL SECURITY	Security lock-ready
DISPLAY INPUT TYPE	1 DisplayPort™ 1.2 in (with HDCP support) 1 HDMI 1.4 (with HDCP support) 1 VGA
DISPLAYPORT™	1 DisplayPort™ 1.2
HDCP	Yes, DisplayPort™ and HDMI
ETHERNET	No
HDMI	1 HDMI 1.4
VGA	1 VGA
CAMERA	No integrated camera
MICROPHONE	No
SPEAKERS	No
WEIGHT	4.14 kg ²
MINIMUM DIMENSIONS (W X D X H)	49.73 x 4.59 x 30.11 cm ³
DIMENSIONS WITH STAND (W X D X H)	49.73 x 21.16 x 45.49 cm

POWER CONSUMPTION	21 W (maximum), 19 W (typical), 0.3 W (standby)
OPERATING TEMPERATURE RANGE	5 to 35°C
OPERATING HUMIDITY RANGE	20 to 80% non-condensing
SUSTAINABLE IMPACT SPECIFICATIONS	Arsenic-free display glass Low halogen Mercury-free display backlights TCO Certified
WHAT'S IN THE BOX	Monitor DisplayPort™ cable HDMI cable AC power cable
MANUFACTURER WARRANTY	3 year limited warranty including 3 year of parts and labour. Certain restrictions and exclusions apply.