

Specifications

Display size (diagonal)	34"
Aspect ratio	21:9
Native resolution	WQHD (3440 x 1440)
Pixel pitch	0.231 mm
Pixels per inch (ppi)	110 ppi
Screen treatment	Anti-glare
Brightness	250 nits
Contrast ratio	3500:1
Display contrast ratio (dynamic)	5000000:1
Curvature	1500R
Backlight type	Edge-lit
Detachable stand	Yes
Height adjustment range	100 mm
Bezel	3-sided micro-edge
Horizontal viewing angle	178°
Vertical viewing angle	178°
Touch-enabled	Not touch-enabled
Response time (typical)	5ms GtG (with overdrive)
Tilt	-5 to +21°
swivel	No swivel
Display features	Low blue light mode Anti-glare Height adjustable
Hardness	3H
Flicker-free	Yes
Panel bit depth	8 bit
pivot	No pivot
Low blue light	Yes (TÜV certified)
VESA mounting	100 mm x 100 mm
Integrated privacy filter	No
Physical security	Security lock-ready
Display Input Type	1 USB Type-C™ (Alternative mode DisplayPort™ 1.2, power delivery up to 65 W) 1 HDMI 2.0 (with HDCP support) 1 DisplayPort™ 1.2 in (with HDCP support) 4 USB-A 3.2 Gen 1
DisplayPort™	1 DisplayPort™ 1.2
HDCP	Yes, DisplayPort™, HDMI and USB Type-C™
USB Type-C® video input	1 SuperSpeed USB Type-C® 5Gbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2)
USB Type-A	4 SuperSpeed USB Type-A 5Gbps signaling rate
Usb b (hub enablement)	1 USB-B
Ethernet	No
Audio port	1 Line Output

HDMI	1 HDMI 2.0
Card reader	No
Camera	No integrated camera
Microphone	No
Speakers	2
Speaker output power	2 x 3 W
Weight	23.17 lb ²
Minimum dimensions (W x D x H)	31.89 x 4.41 x 14.44 in ³
Product dimensions with stand (W x D x H)	31.89 x 9.25 x 20.4 in
Power consumption	190 W (maximum), 48 W (typical), 0.5 W (standby)
Operating temperature range	41 to 95°F
Operating humidity range	20 to 80% non-condensing
Sustainable impact specifications	Arsenic-free display glass Low halogen Mercury-free display backlights TCO Certified TCO Certified Edge
What's in the box	Monitor DisplayPort™ cable HDMI cable Warranty card Quick Setup Poster 1 USB Type-C® to Type-C cable AC power cord