

Specifications

Display size (diagonal)	28"
Aspect ratio	16:9
Native resolution	4K UHD (3840 x 2160) ¹
Pixel pitch	0.116 mm
Pixels per inch (ppi)	157 ppi
Brightness	400 nits
Contrast ratio	1000:1
Display contrast ratio (dynamic)	10000000:1
Curvature	Flat
Backlight type	Edge-lit
Detachable stand	Yes
Height adjustment range	120 mm
Bezel	3-sided micro-edge
Horizontal viewing angle	178°
Vertical viewing angle	178°
Response time (typical)	4ms GtG (with overdrive)
Tilt	-5 to +23°
swivel	±35°
Display features	On-screen controls Low blue light mode Anti-glare
Hardness	3H
Panel bit depth	8 bit
pivot	-90
Low blue light	Yes
VESA mounting	100 mm x 100 mm
Physical security	Security lock-ready
DisplayPort™	1 DisplayPort™ 1.2
USB Type-C® video input	1 SuperSpeed USB Type-C® 5Gbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2)
USB Type-A	3 SuperSpeed USB Type-A 5Gbps signaling rate
Ethernet	No
Audio port	1 Headphone Out Combo Jack
HDMI	1 HDMI 2.0
Card reader	No
Camera	No integrated camera
Microphone	No
Speakers	No
Weight	6.35 kg ⁶
Minimum dimensions (W x D x H)	63.71 x 4.34 x 37.12 cm ⁷
Dimensions With Stand (W x D x H)	63.71 x 18.99 x 53.14 cm
Power consumption	155 W (maximum), 45 W (typical), 0.5 W (standby)
Operating temperature range	5 to 35°C
Operating humidity range	20 to 80% non-condensing

Sustainable impact specifications	Arsenic-free display glass Low halogen Mercury-free display backlights TCO Certified
What's in the box	Monitor DisplayPort™ cable HDMI cable USB Type-C™ cable Warranty card External power supplier Product notice AC power cable
Manufacturer Warranty	1 year limited warranty