

# HP V22v Specs

## Display

---

Size	21.45"
------	--------

---

Panel Type	VA LCD
------------	--------

---

Touchscreen	No
-------------	----

---

Resolution	1920 x 1080
------------	-------------

---

Aspect Ratio	16:9
--------------	------

---

Pixels Per Inch (ppi)	102 ppi
-----------------------	---------

---

Finish	Glossy with Anti-Reflective Coating
--------	-------------------------------------

---

Hardness Rating	3H
-----------------	----

---

Maximum Brightness	250 cd/m <sup>2</sup>
--------------------	-----------------------

---

Contrast Ratio	3000:1
----------------	--------

---

Dynamic Contrast Ratio	8,000,000:1
------------------------	-------------

---

Refresh Rate	60 Hz
--------------	-------

---

Variable Refresh Technology	<i>None</i>
-----------------------------	-------------

---

Bit Depth / Color Support	8-Bit (16.7 Million Colors)
---------------------------	-----------------------------

---

Color Gamut	72% NTSC
-------------	----------

---

Response Time	7 ms (Overdrive)
---------------	------------------

---

Viewing Angle (H x V)	178 x 178°
-----------------------	------------

---

Dot Pitch	0.0831 x 0.241 mm
-----------	-------------------

---

Backlight Lifespan	30,000 Hours
--------------------	--------------

---

## Inputs / Outputs

---

Inputs/Outputs	<b>1 x</b> HDMI 1.4 <b>1 x</b> VGA
----------------	---------------------------------------

---

HDCP Support	Yes
--------------	-----

---

Built-In Speakers	<i>None</i>
-------------------	-------------

---

Memory Card Slots	<i>None</i>
-------------------	-------------

---

Multi-Input Support (PIP/PBP)	<i>None</i>
-------------------------------	-------------

---

## Power

---

Power Consumption	20 W (Maximum)
-------------------	----------------

18.5 W (Typical)

0.5 W (Standby)

---

AC Input Power	100 to 240 VAC, 50 / 60 Hz
----------------	----------------------------

---

Power Adapter Type	External
--------------------	----------

---

USB Power Delivery	<i>None</i>
--------------------	-------------

---

## Environmental

---

Operating Temperature	41 to 95°F / 5 to 35°C
-----------------------	------------------------

---

Operating Humidity	20 to 80%
--------------------	-----------

---

Certifications	BIS, BSMI, CAN ICES-3(A), CB, CCC, CE, CEC, EAC, ENERGY STAR, EPEAT Silver, FCC, GS, Kcc, Microsoft WHQL, NOM, TCO Certified, TUV/S, VCCI, WEEE, cTUVus, as per Manufacturer
----------------	--

---

## Physical

---

Height Adjustment	<i>None</i>
-------------------	-------------

---

Rotation Adjustment	<i>None</i>
---------------------	-------------

---

Swivel Adjustment	<i>None</i>
-------------------	-------------

---

Tilt Adjustment	-5 to 20°
-----------------	-----------

---

Max Arm Extension Length

*None*

---

Mounting-Hole Pattern

100 x 100 mm

---

Lock Slot

Yes

---

Dimensions (W x H x D)

19.9 x 14.5 x 7.1" / 50.5 x 36.8 x 18.0 cm (with Stand)  
19.9 x 11.8 x 1.7" / 50.5 x 30.0 x 4.3 cm (without  
Stand)

---

Weight

6.272 lb / 2.845 kg (with Stand)

---