

Quick Specs

Device Type

White LED edgelight

Features

1 x SuperSpeed USB 5 Gbps (USB3.2 Gen 1) upstream
4 x SuperSpeed USB 5 Gbps (USB3.2 Gen 1)

Panel Type

In-Plane Switching Technology

Aspect Ratio

16:9

Native Resolution

1920 x 1080 at 60 Hz

Pixel Pitch

0.3114 mm x 0.3114 mm

Brightness

300 cd/m² (typical)

Contrast Ratio

1,000:1 (typical)

Response Time

5 ms typical (Fast) (gray to gray)
8 ms (Normal mode) (gray to gray)

Color Support

16.7 Millions

Input Connectors

1 x HDMI 1.4 (HDCP 1.4)
1 x DisplayPort 1.2 (HDCP 1.4)
1 x VGA
1 x SuperSpeed USB 5 Gbps (USB3.2 Gen 1) upstream
4 x SuperSpeed USB 5 Gbps (USB3.2 Gen 1)

Display Position Adjustments

Height adjustability stand 150 mm
Tilt -5° to 21°
Swivel -45° to 45°
Pivot -90° to 90°

Screen Coating

Anti-Glare

Dimensions (WxDxH) - with stand

24.01 in x 7.48 in x 21.03 in

Weight

9.66 lb

Compliant Standards

ENERGY STAR certified monitor

EPEAT Gold registered in the U.S. EPEAT registration varies by country. See www.epeat.net for registration status by country.

RoHS-compliant.

TCO Certified Edge

BFR/PVC free monitor (excluding external cables).

Meets NFPA 99 leakage current requirements.

Arsenic-free glass and Mercury-free for the panel only.

Product Description

Dell 27 Monitor - P2722H

Diagonal Size

27 in

[See less](#)

General

Display Type

LED-backlit LCD monitor / TFT active matrix

Diagonal Size

27"

Built-in Devices

USB 3.2 Gen 1 hub

Panel Type

IPS

Aspect Ratio

16:9

Native Resolution

Full HD (1080p) 1920 x 1080 at 60 Hz

Pixel Pitch

0.3114 mm

Pixel Per Inch

82

Brightness

300 cd/m²

Contrast Ratio

1000:1

Color Support

16.7 million colors

Response Time

8 ms (gray-to-gray normal); 5 ms (gray-to-gray fast)

Horizontal Viewing Angle

178

Vertical Viewing Angle

178

Screen Coating

Anti-glare

Backlight Technology

WLED

Features

LED edgelight system, 99% sRGB color gamut, Flicker Free technology, Mercury free, arsenic-free glass, Dell ComfortView Plus

Dimensions (WxDxH)

24 in x 7.5 in x 21 in - with stand

Weight

14.93 lbs

Connectivity

Interfaces

- DisplayPort
- VGA
- HDMI
- USB 3.2 Gen 1 upstream
- 4 x USB 3.2 Gen 1 downstream

Mechanical

Display Position Adjustments

Height, pivot (rotation), swivel, tilt

Tilt Angle

-5/+21

Swivel Angle

90

Rotation Angle

180

Height Adjustment

5.9 in

VESA Mounting Interface

100 x 100 mm

Miscellaneous

Features

Security lock slot (cable lock sold separately), VESA interface support

Cables Included

- 1 x DisplayPort cable - DisplayPort to DisplayPort - 6 ft
- 1 x USB 3.2 Gen 1 upstream cable

Compliant Standards

RoHS, NFPA 99, DisplayPort 1.2, BFR-free, HDCP 1.4, PVC-free

Power

Input Voltage

AC 100-240 V (50/60 Hz)

Power Consumption (On mode)

15 W

Power Consumption (Typical)

55 Watt

Power Consumption Stand by

0.3 Watt

Power Consumption Sleep

0.3 Watt

Power Consumption (Off Mode)

0.2 Watt

On / Off Switch

Yes

Dimensions & Weight

Dimensions & Weight Details

- With stand - width: 24 in - depth: 7.5 in - height: 21 in - weight: 14.9 lbs
- Without stand - weight: 9.7 lbs

Dimensions & Weight (Shipping)

Shipping Weight

20.52 lbs

Environmental Standards

EPEAT Compliant

EPEAT Gold

ENERGY STAR Certified

Yes

Manufacturer Warranty

Bundled Services

3 years Advanced Exchange Service and Limited Hardware Warranty