

## ADDITIONAL INFORMATION

---

### Memory

Internal memory	128 MB
Flash memory	128 MB

### Printing

Maximum resolution	300 x 300 DPI
Print technology	Thermal transfer
Maximum printing width	10.4 cm

### Weight & dimensions

Weight	11.34
Height	277 mm
Width	242 mm
Depth	432 mm

### Operational conditions

Operating relative humidity (H-H)	20 - 85%
Storage temperature (T-T)	-40 - 60 °C
Operating temperature (T-T)	5 - 40 °C
Storage relative humidity (H-H)	5 - 85%

### Ports & interfaces

Optional connectivity	Ethernet, Parallel
Connectivity technology	Wired & Wireless
USB 2.0 ports quantity	1
RS-232 ports	1

### Performance

Built-in barcodes	1D, 2D, Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, TLC39, UPC-A, UPC-E
Ribbon length	450 m
Ribbon width	11 cm

### Design

Type	simple
------	--------

### Display

Display	LCD
---------	-----

### Technical details

Certification	IEC 60950, EN 55022 B, EN 55024, EN 61000-3-2, EN 61000-3-3, cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S Mark, CCC, GOST-R, KCC, BSMI
Colour of product	Black, White

### Certificates

Energy Star certified	Yes
-----------------------	-----

### Paper handling

Media thickness	0.076 - 0.025
Maximum label width	11.4 cm
Maximum label length	0.991 m
Maximum media length	185.4 cm