

Specifications

Scanning	
Wavelength	610 nm
Yaw reading angle	-45 - 45 °
Pitch reading angle	-65 - 65 °
Tilt reading angle	-65 - 65 °
Sensor type	LED
Scanner type	1D/2D
Optical sensor resolution	1280 pixels
Type	Handheld bar code reader
Linear (1D) barcodes supported	CODABAR
Linear (1D) barcodes supported	Code 11
Linear (1D) barcodes supported	Code 128
Linear (1D) barcodes supported	Code 39
Linear (1D) barcodes supported	code 93
Linear (1D) barcodes supported	GS1-128 (UCC/EAN-128)
Linear (1D) barcodes supported	MSI
Linear (1D) barcodes supported	Plessey
Linear (1D) barcodes supported	U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code
2D (matrix & stacked) barcodes supported	Composite Codes
2D (matrix & stacked) barcodes supported	Data Matrix
2D (matrix & stacked) barcodes supported	Han Xin
2D (matrix & stacked) barcodes supported	MaxiCode
2D (matrix & stacked) barcodes supported	Micro QR Code
2D (matrix & stacked) barcodes supported	MicroPDF417
2D (matrix & stacked) barcodes supported	PDF417
2D (matrix & stacked) barcodes supported	QR Code

2D (matrix & stacked) barcodes supported	TLC-39
Ports & interfaces	
Ethernet LAN	True
Standard interfaces	RS-232,USB,Keyboard wedge
Bluetooth Low Energy (BLE)	True
Bluetooth version	4.0
Connectivity technology	Wired & Wireless
Wireless range	100 m
Power	
Battery capacity	3100 mAh
Battery technology	Lithium-Ion (Li-Ion)
Number of reads per charge	100000
Power source type	Battery
Operational conditions	
Operating relative humidity (H-H)	5 - 95 %
Storage temperature (T-T)	-40 - 70 °C
Operating temperature (T-T)	-20 - 50 °C
Performance	
Product colour	black
Product colour	Green
Programming function	True
International Protection (IP) code	IP67
LED indicators	Y
Protection features	Dust resistant
Protection features	Shock resistant
Protection features	Water resistant
Weight & dimensions	
Weight	407 g
Width	142 mm

Depth	76 mm
Height	185 mm
Technical details	
Sustainability certificates	RoHS