

## ADDITIONAL INFORMATION

### Technical details

Interface	USB
Cables included	USB
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code, Composite Codes, Data Matrix, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Certification	UL60950-1 2nd ed, CSA C22.2 No. 60950-1 2nd ed, EN60950-1/IEC60950-1 2nd ed.\n\nIEC 62471:2006 and EN 62471:2008\n\nFCC Part 15 Class B, ICES-003 Class B,\n\nEN55022 Class B, EN55024, Medical\n\nElectrical Equipment: EN60601-1-2
LED indicators	1
Colour of product	Black

### Scanning

Scanner type	1D and 2D (bidimensional codes)
Yaw reading angle	-60 - 60°
Pitch reading angle	-65 - 65°
Motion tolerance (cm/s)	76.2

### Power

Input voltage	5
Power consumption	360 mA

### Performance

Buzzer	Yes
--------	-----

### Weight & dimensions

Weight	162 g
Height	165 mm
Width	67 mm
Depth	98 mm

### Operational conditions

Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-40 - 70 °C
Operating temperature (T-T)	0 - 50 °C

### Ports & interfaces

Connectivity technology	Wired
-------------------------	-------

### Design

Type	simple
RoHS compliance	Yes