

SENNHEISER SDW 5066 Specs

Headset Features

Hearing Protection, Noise Cancellation

Microphone

Microphone Design

Boom

Microphone Frequency Response

150 Hz to 3.5 kHz (Narrowband)
100 Hz to 7.5 kHz (Wideband)
100 Hz to 11 kHz (Super Wideband)

Speaker

Earpiece Design

On-Ear

Listening Mode

Binaural

Speaker Frequency Response

150 Hz to 11.5 kHz (Super Wideband)
150 Hz to 7.5 kHz (High-Density Wideband)
150 Hz to 7.5 kHz (Wideband)
150 Hz to 3.5 kHz (Narrowband)
20 Hz to 20 kHz (Fullband)

Maximum Sound Pressure Level
(SPL)

118 dB

Connectivity

Wireless Range	590' / 179.8 m
----------------	----------------

Wireless Technology	DECT
---------------------	------

Host Connection	1 x USB Type-A
-----------------	-----------------------

Power

Recharge Time	1.5 Hours
---------------	-----------

Standby Time	44 Hours
--------------	----------

Talk Time	9 to 14 Hours
-----------	---------------

Environmental

Operating Temperature	41 to 113°F / 5 to 45°C
-----------------------	-------------------------

Storage Temperature	-4 to 158°F / -20 to 70°C
---------------------	---------------------------

General

Wearing Style	Over-the-Head
---------------	---------------

Encryption Bit Depth	128-Bit
----------------------	---------

Physical

Ear Pad Size 2.1" / 54.5 mm

Weight 4.8 oz / 136 g (Headset)
