

SENNHEISER SDW 5016 Specs

Headset Features

Hearing Protection, Noise Cancellation

Microphone

Microphone Design

Boom

Microphone Frequency Response

150 Hz to 3.5 kHz (Narrowband)
100 Hz to 7.5 kHz (Wideband)
100 Hz to 11 kHz (Super Wideband)

Speaker

Earpiece Design

On-Ear

Listening Mode

Monaural

Speaker Frequency Response

100 Hz to 11 kHz (Super Wideband)
100 Hz to 7.5 kHz (High-Density Wideband)
100 Hz to 7.5 kHz (Wideband)
150 Hz to 3.5 kHz (Narrowband)

Maximum Sound Pressure Level
(SPL)

118 dB

Connectivity

Wireless Range	590' / 179.8 m
----------------	----------------

Wireless Technology	DECT
---------------------	------

Host Connection	1 x USB Type-A
-----------------	-----------------------

Power

Recharge Time	1 Hour
---------------	--------

Standby Time	48 Hours
--------------	----------

Talk Time	6 to 10 Hours
-----------	---------------

Environmental

Operating Temperature	41 to 113°F / 5 to 45°C
-----------------------	-------------------------

Storage Temperature	-4 to 158°F / -20 to 70°C
---------------------	---------------------------

General

Wearing Style	Ear Hook, Over-the-Head, Behind-the-Head
---------------	--

Encryption Bit Depth	128-Bit
----------------------	---------

Physical

Ear Pad Size 2.1" / 53 mm

Weight 2.0 oz / 58 g (Headset)
