

### Voyager 1202g

### Wireless Single-Line Laser Scanner

Honeywell's Voyager™ 1202g single-line laser scanner incorporates the freedom of Bluetooth® wireless technology and offers a field-replaceable battery that can be quickly and easily exchanged. The new 1202g delivers the aggressive linear bar code scanning that users have come to expect from the world-renowned Voyager family of scanners.

Voyager 1202g incorporates a Bluetooth® Class 2, v2.1 radio, enabling unrestricted movement up to 10 meters (33 feet) from the base. Honeywell has also demonstrated Bluetooth® Class 2 communication ranges of up to 30 meters (100 feet) with a clear line of sight from the base. The 1202g offers users added safety and a wider range of movement by eliminating tethered cables. For added convenience, the included paging system helps locate misplaced scanners with visual and auditory signals.

The field-removable battery can be exchanged quickly and easily, without the use of tools. The user-preferred, long-lasting Lithium ion battery provides 12 hours or more of scanning time and 45,000 scans per charge. The 1202g recharges quickly, resulting in increased throughput.

Built on the platform of the corded Voyager 1200g, the 1202g is optimized for scanning linear bar codes, including poorly printed and damaged codes. Voyager 1202g allows enterprises to minimize manual data entry, leading to increased productivity and reduction in errors.

This plug and play scanner incorporates a multi-interface design with automatic interface detection. Voyager 1202g automatically configures itself to the appropriate interface, shortening the installation process. 1202g's easy installation will benefit users in environments such as retail stores, hospitals, and light manufacturing facilities. The base can be desk or wall mounted to accommodate a variety of workstation layouts.



### **Features**

- Bluetooth® Wireless Technology: Facilitates scanning
  of all standard 1D bar codes 10 meters (33 feet) or more
  away from the base, depending on the user's environment
- Long Battery Life and Tool-Free Battery Removal: The
  user-preferred Lithium ion battery provides 12 hours or
  more of use, depending on scanning volume, and the
  field-replaceable battery can be exchanged quickly and
  easily, without the use of tools
- Automatic Interface Configuration: Supports all popular interfaces in one device, replacing the time consuming process of scanning programming bar codes with automatic interface detection and configuration
- Excellent Poor Quality Code Reading: Increases throughput and reduces the potential for hand-keyed errors by quickly scanning a variety of 1D bar codes, including those that are damaged or smudged
- Paging Functionality: Simply press the button on the base to locate your lost scanner; Voyager 1202g responds with a series of beeps and blinking lights on its indicator panel
- Remote MasterMind™ Ready: Reduces total cost of ownership by providing a turnkey remote device management solution that easily manages and tracks usage of installed devices

### **Voyager 1202g Technical Specifications**

| Radio/Range   | 2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1; Class 2: 10m (33') line of sight  |   |
|---|--|---|
| Data Rate (Transmission Rate)   | Up to 3 Mbps   |   |
| Battery   | 1800 mAh Lithium ion minimum   |   |
| Number of Scans   | Up to 45,000 scans per charge  |   |
| Expected Hours of Operation   | 12 hours   |   |
| Expected Charge Time  | 4 hours  |   |
| /lechanical/Electrical  |  |   |
|   | Scanner: Voyager 1202g   | Charge and Communication Base: CCB00-010BT  |
| Dimensions (LxWxH)  | 180 mm x 66 mm x 92 mm (7.1" x 2.6" x 3.6")  | 200 mm x 67 mm x 97 mm (7.9" x 2.6" x 3.8")   |
| Weight  | 180 g (6.3 oz) (includes battery)  | 185 g (6.5 oz)  |
| Operating Power (Charging)  | N/A  | 5 W (1 A @ 5 V with power supply); 2.5W (0.5 A @ 5 with USB)  |
| Non-Charging Power  | N/A  | 0.625 W (0.125 A @ 5 V)   |
| Host System Interfaces  | N/A  | USB, Keyboard Wedge, RS232, IBM 46xx (RS485)  |
| Environmental   |  |   |
| THE THIRD THE   |  |   |
| arra di montal  | Scanner: Voyager 1202g   | Charge and Communication Base: CCB00-010BT  |
| Operating Temperature   | Scanner: Voyager 1202g<br>5°C to 40°C (41°F to 104°F)  | Charge and Communication Base: CCB00-010BT<br>Charging: 5°C to 40°C (41°F to 104°F);<br>Non-Charging: 0°C to 50°C (32°F to 122°F)   |
|   |  | Charging: 5°C to 40°C (41°F to 104°F);  |
| Operating Temperature   | 5°C to 40°C (41°F to 104°F)  | Charging: 5°C to 40°C (41°F to 104°F);<br>Non-Charging: 0°C to 50°C (32°F to 122°F)   |
| Operating Temperature Storage Temperature with Battery  | 5°C to 40°C (41°F to 104°F) -5°C to 35°C (23°F to 95°F)  | Charging: 5°C to 40°C (41°F to 104°F);<br>Non-Charging: 0°C to 50°C (32°F to 122°F)<br>-5°C to 35°C (23°F to 95°F)  |
| Operating Temperature<br>Storage Temperature with Battery<br>Humidity   | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing   | Charging: 5°C to 40°C (41°F to 104°F);<br>Non-Charging: 0°C to 50°C (32°F to 122°F)<br>-5°C to 35°C (23°F to 95°F)<br>0 to 95% relative humidity, non-condensing  |
| Operating Temperature<br>Storage Temperature with Battery<br>Humidity<br>Drop   | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5′) drops to concrete  | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete      |
| Operating Temperature Storage Temperature with Battery Humidity Drop Environmental Sealing  | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5′) drops to concrete  IP42  | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete IP42 |
| Operating Temperature Storage Temperature with Battery Humidity Drop Environmental Sealing Light Levels   | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5′) drops to concrete  IP42  | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete IP42 |
| Operating Temperature Storage Temperature with Battery Humidity Drop Environmental Sealing Light Levels Scan Performance  | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5′) drops to concrete  IP42  0 to 70,000 lux (6,500 foot-candles)  | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete IP42 |
| Operating Temperature Storage Temperature with Battery Humidity Drop Environmental Sealing Light Levels Scan Performance Scan Pattern                                     | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5') drops to concrete  IP42  0 to 70,000 lux (6,500 foot-candles)  Single scan line  | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete IP42 |
| Operating Temperature  Storage Temperature with Battery  Humidity  Drop  Environmental Sealing  Light Levels  Can Performance  Scan Pattern  Scan Speed (laser only)      | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5′) drops to concrete IP42  0 to 70,000 lux (6,500 foot-candles)  Single scan line  100 scan lines per second                  | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete IP42 |
| Operating Temperature  Storage Temperature with Battery Humidity Drop Environmental Sealing Light Levels Scan Performance Scan Pattern Scan Speed (laser only) Scan Angle | 5°C to 40°C (41°F to 104°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1.5 m (5°) drops to concrete IP42  0 to 70,000 lux (6,500 foot-candles)  Single scan line  100 scan lines per second  Horizontal: 30° | Charging: 5°C to 40°C (41°F to 104°F); Non-Charging: 0°C to 50°C (32°F to 122°F)  -5°C to 35°C (23°F to 95°F)  0 to 95% relative humidity, non-condensing  Designed to withstand 30 1 m (3.3′) drops to concrete IP42 |

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies




#### For more information:

www.honeywellaidc.com

### **Honeywell Scanning & Mobility**

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com







# Solutions for Automatic Identification, Barcodes and Mobility

More than 15,000 customers in 15 countries • More than 60,000 products in stock



800 729 0236 www.logiscenter.us



020 3318 8265 www.logiscenter.co.uk



911 433 048 www.logiscenter.com



0241 9550 9225 www.logiscenter.de



0720 115814 www.logiscenter.at



02 4792 1697 www.logiscenter.it



01 82 88 44 70 www.logiscenter.fr



02 58 80 583 www.logiscenter.be



308 800 842 www.logiscenter.pt

### **About LOGISCENTER**

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

# All Brands Technical Service

### Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permament stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.

### **Our Brands**





**EPSON** 





PRINTRONIX







**TOSHIBA** 



## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



PVC card printers



Barcode readers



RFID



Data terminals & PDA



Consumables (labels, ribbons, PVC cards)