

Model Configuration

Model	B405V_DN
Print speed	up to 45 ppm
Recommended monthly print volume	Up to 15,000 pages
Duty cycle	Up to 150,000 images/month [Ⓞ]
Processor speed	1.05 GHz
Print memory (standard)	2 GB standard
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, NFC Tap-to-Pair (optional: Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported))
Two-sided output	Standard

Copy

Maximum copy resolution	600 x 600 dpi
First-page-out time, copying	As fast as 6.2 seconds
Copy features	Automatic Background Suppression, Book Copying with Center Erase, Collation, Darkness Control, Edge Erase, ID Card Copy, Image Shift, N-up, Original Type,

Print

Maximum print resolution	1200 x 1200 dpi
First-page-out time, printing	As fast as 5.1 seconds
Page Description Languages (PDL)	Adobe® PostScript® 3™, HP-GL, JPEG, PCL® 5e, 6, PDF, TIFF, XPS
Print features	Application defaults, Bi-directional real-time status, Booklet creation, Draft mode, Job Monitoring, Job identification, Personal print, Print from USB, Sample set, Saved job, Scaling, Secure Print, Skip blank pages, Store and Recall driver settings, Two-sided Printing (default), Xerox® Earth Smart Driver Settings
Mobile printing	<u>Apple® AirPrint™</u> , <u>Google Cloud Print™</u> , <u>Mopria®</u> , <u>Xerox® Print Service Plug-in for Android™</u> (optional: @PrintByXerox, WiFi Direct® [with optional Wi-Fi Kit], Xerox® Mobile Print Cloud, Xerox® Mobile Print Solution)

Scan

Scan destinations	Scan to Home, Scan to Network (FTP or Browse SMB), Scan to USB, Scan to email
--------------------------	---

Fax

Fax features	Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts), LAN Fax, Walk-up Fax*
---------------------	--

	* - Analog phone line required.
Fax compression	MH, MR, MMR, JBIG

Print Drivers

OS support	HP UX® 11, HP UX® 11i, IBM AIX® 5, Mac OS® X 10.5 and later, including OS 12, Redhat Enterprise 4 and 5, Solaris 10, Solaris 9, Ubuntu®, Windows® 11, Windows® 2003 Server, Windows® 2008 Server, Windows® 7, Windows® Vista, Windows® XP, Xerox Global Printer Driver, Xerox Mobile Express Driver
-------------------	---

Font capabilities

PostScript® fonts	144
PCL® fonts	82

Media Handling

Output capacity	250 sheets
Document handler	Reversing Automatic Document Feeder (RADF) Capacity: 60 sheets 139.7 x 139.7 mm to 216 x 356 mm
Paper capacity	Tray (Multipurpose tray): 150 sheets Tray 1 : 550 sheets Tray 2 (optional): 550 sheets Tray 3 (optional): 550 sheets Tray 4 (optional): 550 sheets
Paper size	Tray (Multipurpose tray): Custom sizes: 76.2 x 127 mm to 216 x 356 mm Tray 1 : Custom sizes: 76.2 x 127 mm to 216 x 356 mm

Tray 2 (optional): Custom sizes: 139.7 x 210 mm to 216 x 356 mm

Tray 3 (optional): Custom sizes: 139.7 x 210 mm to 216 x 356 mm

Tray 4 (optional): Custom sizes: 139.7 x 210 mm to 216 x 356 mm

Security

Security features	256-bit Encryption, Access controls, Audit log, Automatic Self-Signed Certificate Creation, Certificate Path Validation, Certificate Revocation Settings, Domain Filtering, FIPS 140-2, Firmware Verification, IP Address Filtering, Network authentication, Port Filtering, Role based permissions, SNMPv3, Secure Email, Secure Fax, Secure Print, Secure Scan, Security certificates, Smart Card Enablement Kit (CAC/PIV/.NET), TLS
--------------------------	--

Electrical

Power consumption	Operating: 620 W Standby: 60 W Power save: as low as 0.83 W
ENERGY STAR	ENERGY STAR® qualified

Operating Environment

Temperature (operating)	10 - 32 ° C
Relative humidity (operating)	10 - 85 % RH (noncondensing)

Dimensions

Dimensions	495 x 495 x 551 mm
-------------------	--------------------

(WxDxH)	
Weight	22 kg