

General

Model		AR-7024D	AR-7024
Type		Desktop	
Engine speed	A4 (8 1/2" x 11")*1	Max. 24 ppm	
	A3 (11" x 17")	Max. 12 (11) ppm	
Control panel display		Custom LCD	
Paper size		Max. A3 (11" x 17"), min. A6*2 (5 1/2" x 8 1/2")	
Paper capacity (80 g/m ²)	Standard	350 sheets (250-sheet tray and 100-sheet multi-bypass tray)	
	Maximum	1,850 sheets (350 sheets & optional 500-sheet tray x 3)	
Paper weight	Tray	55 g/m ² to 105 g/m ² (13 lbs bond to 28 lbs bond)	
	Multi-bypass tray	55 g/m ² to 200 g/m ² (13 lbs bond to 110 lbs index)	
Warm-up time*3		25 sec.	
Memory	Standard	64 MB	
	Maximum	448 MB*4	
Power requirements		Rated local AC voltage $\pm 10\%$, 50/60 Hz	
Power consumption		Max. 1.2 kW	
Dimensions (W x D x H)*5		599 x 612 x 511 mm (23 19/32" x 24 7/64" x 20 1/8")	
Weight (approx.)*5		29 kg (64.0 lbs)	28 kg (61.8 lbs)

Copier

Model		AR-7024D	AR-7024
Original paper size		Max. A3 (11" x 17")	
First copy time*6	A4	6.4 seconds	
	8 1/2" x 11"	6.5 seconds	
Continuous copy		Max. 999 copies	
Resolution		600 x 600 dpi	
Gradation		256 levels	
Zoom range		25% to 400% (50% to 200% using RSPF) in 1% increments	
Preset copy ratios*7	Metric	10 ratios (5R/5E)	
	Inch	10 ratios (5R/5E)	

Scanner

Model		AR-7024D	AR-7024
Resolution	Push scan	75, 100, 150, 200, 300, 400, 600 dpi	
	Pull scan	75, 100, 150, 200, 300, 400, 600 dpi; 50 dpi to 9,600 dpi via user setting*8	
File formats		TIFF, PDF, JPEG*9, BMP*10	
Scan destinations		Scan to e-mail*11/desktop*12/FTP server*11/USB drive*11	

Printer

Model		AR-7024D	AR-7024
Resolution		600 x 600 dpi	
Interface		USB 2.0 (host, high-speed), 10Base-T*11/100Base-TX*11	
Supported OS*13		Windows Server® 2012, Windows Server® 2012 R2, Windows Server® 2016, Windows Server® 2019, Windows® 8.1, Windows® 10, Mac OS 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15	
Network protocols*11		TCP/IP	
PDL		SPLC (Sharp Printer Language with Compression), PCL 6 emulation*14, PostScript® 3™ emulation*15	
Available fonts		80 fonts for PCL*14, 136 fonts for PostScript 3 emulation*15	