

## Specifications

Frequency Range (-10dB)	35 Hz – 20 kHz
Frequency Response ( $\pm 3$ dB)	55 Hz – 19 kHz
Coverage Pattern	90° x 50°, rotatable waveguide
Directivity Factor (Q)	12.6
Directivity Index (DI)	11 dB
Crossover Frequency	1.2 kHz
System Power Rating	600 W (2400 W peak), 100 hrs
Maximum SPL (1m)	128 dB-SPL cont avg (134 dB peak)
System Sensitivity (1w @ 1m)	100 dB SPL
Transformer Taps	70V: 400 W, 200 W, 100W100V: 400W, 200W
LF Driver	1 x JBL 2265H 380 mm (15 in.) Differential Drive® driver with 75 mm (3 in) dual voice coil
Nominal LF Driver Impedance	8 ohms
LFD Sensitivity (1W @ 1m, within operational band)	98 dB SPL
HF Driver	JBL 2432H, 38 mm (1.5 in) exit compression driver, 75 mm (3 in) voice coil
Nominal HF Driver Impedance	8 ohms
HFD Sensitivity (1W @ 1m)	113 dB SPL
Waveguide	PT-H95HF-1
Enclosure	Hand-Laminated Fiberglass, gray gelcoat (black available)
Suspension Attachment	2 x M10 for Included U-Bracket, 2 x M6 for aiming stabilization, 1 x M10 on rear for safety.
Grille	Three layer grille assemblies consisting of 14-gauge powder coated stainless steel. backed with open cell foam and stainless steel

Input Connector	CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs.
Environmental	IP56 per IEC 529
Dimensions (H x W x D in horizontal cabinet orientation)	485 x 810 x 478 mm(19.1 x 31.9 x 18.8 in)
Net Weight	28.3 kg (62.5 lb)
Crossover Modes	Passive