

Technical Specifications

[Download Product Manual](#)

- Custom, All-Brass K67-Inspired Capsule
- Capsule Makeup: Gold Sputtered, Dual Large Diaphragm, Single Backplate, 6 Microns NOS Mylar (PET Film)
- Custom Transformer From Lundahl Sweden
- New-Old-Stock 6AU6 Vacuum Tube
- Gotham 5 Meter GAC-7, 7-Pin Tube Microphone Cable
- Wima Capacitors
- Self-Noise: 15dB (A-Weighted) Cardioid, 17dB (A-Weighted) Omni
- Polar Patterns: 2 Patterns - Cardioid, Omni
- Dynamic Range: 113dBA
- Maximum SPL: 131dB (Cardioid), 134dB (Omni)
- Frequency Range: 20 Hz~20 KHz
- Output Impedance: 100 ohms
- Rated Load Impedance: $\geq 1k\Omega$

- S/N Ratio: 76dB (Cardioid), 73dB (Omni)
- External IEC Grounded PSU
- Total Weight: 13.3Lbs
- Mic Length: 7.5 Inches
- Mic Diameter: 2.5 Inches
- Includes: WA-8000 Microphone, External Power Supply, IEC Power Cable, Shock Mount, Gotham GAC-7 Cable, And Custom Hard Case