

JBL VT488 Specs

PA Speaker

Configuration Passive Dual Subwoofer

Enclosure Type Bass-Reflex Line Array Subwoofer

Total Power Capacity **Passive:**
8000 W Peak
2000 W RMS

System Impedance **LF:**
2 x 8 Ohms (Nominal)

Drivers

LF Driver **2 x 12" / 304.8 mm Woofer**

LF Voice Coil Dual 3" / 76.2 mm

Magnet Neodymium

Performance

Frequency Range 35 Hz to 300 kHz -10 dB

Frequency Response	40 Hz to 300 kHz \pm 3 dB
--------------------	-----------------------------

Maximum SPL	139 dB (Peak, Half-Space)
-------------	---------------------------

Speaker Sensitivity	Passive: 95 dB
---------------------	--------------------------

Connectivity

Audio I/O	3 x speakON NL4 Speaker Input/Thru/Output 2 x speakON NL8 Speaker Input/Thru
-----------	---

Signal Processing

Dynamic Processing	Multiband Limiter
--------------------	-------------------

Alignment Delay	0 to 2000 ms
-----------------	--------------

Digital Signal Processing	32-Bit Floating Point DSP: FIR Filter, User Settings (Adjustable via Optional Software)
---------------------------	--

Maximum Sampling Rate	96 kHz / 24-Bit
-----------------------	-----------------

Physical

Mounting	<i>None</i>
----------	-------------

Handles	4
---------	---

Construction Material

Composite, Metal Grille, Plywood

Dimensions

15.7 x 22.8 x 25.3" / 398.8 x 579.1 x 642.6 mm

Weight

65 lb / 29.5 kg

Packaging Info

Package Weight

80 lb

Box Dimensions (LxWxH)

30 x 25.5 x 20.3"
