

Specifications

Power Rating	800 W / 1600 W / 3200W
Frequency Range (-10dB)	60 Hz - 20 kHz
Dimensions (H x W x D)	629 mm x 432 mm x 324 mm (375 mm stage height) 24.75 in x 17 in x 12.75 in (14.75" stage height)
Coverage Pattern (-6 dB)	50° x 90° nominal
Crossover Modes	Passive / Bi-amp
Crossover Frequency	1.1 kHz
Maximum SPL (1m)	127 dB SPL continuous (133 dB SPL peak)
Sensitivity	98 dB SPL
LF Driver	1 x JBL 2265H 380 mm (15 in) Differential Drive® woofer 8 Ohms
HF Driver	1 x JBL 2453H-SL, 38 mm (1.5 in) exit compression driver, 100 mm (4 in) voice coil and neodymium magnet
Nominal Impedance	8 ohms
Active Tunings	Tunings available at www.jblpro.com
Enclosure	Symmetrical stage monitor, 15/18 mm, plywood
Finish	Black DuraFlex™ finish
Grille	Powder coated, black, 16 gauge perforated steel with acoustically transparent black screen backing
Inputs	Neutrik® Speakon® NL-4 (x2), one on each end
Net Weight (each)	21 kg (46.0 lb)
Outputs	1 x XLR