

Specifications

Power Rating	800 W / 1600 W / 3200 W
Frequency Range	31 Hz – 220 Hz
Dimensions (H x W x D)	508 mm x 597 mm x 749 mm (20.0 in x 23.5 in x 29.5 in)
Frequency Range (-10dB)	31 Hz – 220 Hz
Recommended Crossover Frequencies	80 Hz, 24 dB / octave HPF80 Hz, 24 dB / octave LPF
System Maximum SPL	130 dB SPL peak
System Sensitivity (1w @ 1m)	95 dB SPL
LF Driver	1 x JBL 2268H 457 mm (18 in) Differential Drive woofer
Nominal Impedance	8 ohms
Active Tunings	Tunings available at www.jblpro.com
Enclosure	Rectangular, 18 mm, 13-ply birch plywood
Suspension / Mounting	Optional VRX932LA-AF line array frame kit or 10mm eyebolt
Finish	Black DuraFlex™ finish
Grille	Powder coated, black, 16-gauge perforated steel with acoustical transparent charcoal foam backing.
Inputs	Neutrik® Speakon® NL-4 (x2)
Net Weight (each)	37 kg (81 lb)
Optional Accessories	SRX718S-CVR: Pull-over padded cover SS4-BK: Adjustable, heavy-duty pole, M20 thread to 35 mm WK-4: Caster kit VRX-AF: Array Frame Kit M-10 eyebolt kit
Outputs	1 x XLR