

## Specifications

Power Rating	1500 Watts PeakLF: Dual-Bridged Technology™, Class D
Frequency Range	31 Hz – 220 Hz
Dimensions (H x W x D)	508 mm x 597 mm x 749 mm (20.0 in x 23.5 in x 29.5 in)
Frequency Range (-10dB)	31 Hz – 220 Hz
Maximum Peak Output	126 dB SPL at 1m
Bandpass Nominal Impedance	LF: 2 x 2 ohms
LF Driver	1 x JBL 2268FF 457 mm (18 in) dual voice coil Differential Drive® woofer with neodymium-magnet
Inputs	XLR with loop through
User Controls	Input Attenuator (0-16 dB)Selectable 80 Hz or 120 Hz Low Pass 80 Hz High-Pass enable/disable for XLR loop thru.
System Processing	DSP based, resident in Input Module
System Management	DSP based limiters for mechanical and thermal protection
AC Power Operating Range	90-132 VAC or 216-264 VAC, 50/60Hz
AC Line Voltage	User selectable: 120V/240V (-15%, +10%)
AC Input Connector	Neutrik PowerCon (NAC 3MPA)
AC Loop Through Connector	Neutrik PowerCon (NAC 3MPB)
AC Current Requirements	6A per system at 120V, 3A per system at 240V

Suspension / Mounting	Optional VRX-AF line-array frame kit or 10 mm forged eyebolts
Finish	Black DuraFlex™ finish
Grille	Powder coated, black, 16-gauge perforated steel with acoustically transparent foam
Net Weight (each)	38.5 kg (85 lb)
Optional Accessories	VRX-AF array frameSRX718S-CVR: Pull-over padded cover (works with WK-4S) SS4-BK adjustable satellite speaker pole WK-4S Caster kit
Outputs	1 x XLR
Nominal Impedance	LF: 2 x 2 ohms