

Specifications

Power Rating	400 W / 800 W / 1600W
Frequency Range (-10dB)	70 Hz - 20 kHz
Dimensions (H x W x D)	230mm x 420mm x 270mm (9.0in x 16.5in x 10.5in)
Coverage Pattern	100 x 15 nominal
Frequency Response (± 3 dB)	85 Hz - 19 Hz
Crossover Modes	Bi-amp / passive,
Crossover Frequency	2.0 kHz
Net Weight (each)	12.7 kg (28 lb)
Inputs	Neutrik® Speakon NL-4 (x2)
Outputs	1 x XLR
Enclosure	Duraflex coated plywood
System Type	Constant Curvature 8" Two-Way Line Array System
Maximum SPL (1m)	122 dB SPL peak (passive mode) LF: 122 dB (bi-amp mode) HF: 128 dB (bi-amp mode)
Nominal Impedance	Passive = 8 ohm Bi-amp LF = 8 ohm Bi-amp HF = 16 ohm
LF Driver	1 x 200 mm (8 in) Differential Drive® woofer
HF Driver	2 x 25 mm (1.0 in) neodymium compression driver
Suspension / Mounting	Dual 36 mm pole socket included. Suspension requires optional VRX-SMAF line array frame kit or M10 eyebolts.