

Specifications

Power Rating	800 W / 1600 W / 3200 W
Frequency Range (-10dB)	57 Hz - 20 kHz
Dimensions (H x W x D)	343mm x 597mm x 376mm (13.5in x 23.5in x 14.8in)
Frequency Response (± 3 dB)	75 Hz - 20 Hz
Coverage Pattern	100 x 15 nominal
Crossover Modes	Bi-amp / passive, externally switchable
Crossover Frequency	132 dB SPL peak 1.2 kHz
Maximum SPL (1m)	130 dB SPL peak (passive mode) LF: 130 dB HF: 139 dB
Sensitivity	Passive: 95 dB SPL Bi-amp LF: 95 dB SPL Bi-amp HF: 114 dB SPL
LF Driver	1 x JBL 2262H 305 mm (12 in) Differential Drive® woofer with neodymium magnet, dual voice-coils, and dual magnetic gaps.
HF Driver	3 x JBL 2408J, 38 mm (1.5 in) voice-coil, neodymium compression driver
Nominal Impedance	Passive = 8 ohm Bi-amp LF = 8 ohm Bi-amp HF = 8 ohm
Active Tunings	Tunings available at www.jblpro.com
Enclosure	18 mm, 11-ply birch plywood
Suspension / Mounting	Optional VRX932LA-AF line array frame kit
Finish	Black DuraFlex™ finish

Grille	Power coated, black, 16-guage perforated steel with with acoustically transparent foam
Inputs	Neutrik® Speakon® NL-4 (x2)
Net Weight (each)	21 kg (46 lb)
Optional Accessories	VRX932LA-AF: Suspension array frame SS2-BK: Tripod speaker stand SS3-BK: Satellite speaker pole,41 in (1041 mm) SS4-BK: Adjustable satellite speaker pole to be used with the SRX718S only
Outputs	1 x XLR
System Type	Constant Curvature 12" Two-Way Line Array System